

# NHMICD2-615 / NHMID2-620

6" Marquise II IC Air-Tight Double Wall New Construction Housing

Source: 18W or 24W LED  
1500lm or 2000lm

Type

Project

Catalog No.

Notes

## PRODUCT DESCRIPTION

Dedicated new construction housing for use in insulated ceilings can be in direct contact with thermal insulation. Air-tight construction provides energy savings by reducing the flow of air through the ceiling.

## CONSTRUCTION

**Plaster Frame:** 0.040 steel frame with integral bar hanger brackets. Brackets can accommodate longer 27" accessory flat bar hangers. Brackets run along all sides of frame to allow bar hangers to be run parallel or perpendicular to junction box.

**Housing:** 0.040 aluminum outer housing with white powder coated steel inner housing. Inner housing adjusts for ceiling thickness from 1/2" to 1-1/4". Inner housing supports the reflector assembly's torsion springs.

**Air Flow Restriction:** Housing has factory installed gaskets to restrict airflow from room into ceiling plenum to <2CFM (cubic feet per minute) in accordance with ASTM-283 Air-Tight requirements.

**Clearance:** "IC" Insulated ceiling housings are direct contact rated; no minimum clearance is required.

**Bar Hangers:** Two 13-3/4" to 24-1/2" adjustable bar hangers with captive nails are included on frame. Bar hangers are parallel to junction box, but can be repositioned 90° perpendicular to junction box if desired. "L" Shaped bar hanger foot to align to bottom of construction joist. A T-Bar notch allow for easy installation in a suspended ceiling.

**Junction Box:** Prewired 25 cubic inch 0.064" thick galvanized steel, with five 1/2", two 3/4" knockouts, four Romex® pryouts, and snap on covers. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Maximum of 8 no. 12 AWG through branch circuit conductors suitable for at least 90°C permitted in junction box.

## ELECTRICAL

**Input Voltage:** 120V or 120-277V

**Lumens / Wattage:**

NHMICD2-615 = 1500lm / 18W

NHMICD2-620 = 2000lm / 24W

**Operating Temp.:**

NHMICD2-615 = 0°C to 40°C ambient temperature

NHMICD2-620 = 0°C to 35°C ambient temperature

**Dimming:** Triac, ELV or 0-10V

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

## COMPATIBLE REFLECTORS

### CATALOG NO. DESCRIPTION

<a href="#">NRM2-611</a>	6" Round Open Reflector
<a href="#">NRM2-612</a>	6" Round Baffle
<a href="#">NRM2-618</a>	6" Round Open Reflector for Decorative Glass (1500lm only)
<a href="#">NRM2-614</a>	6" Round Surface Adjustable (1500lm only)
<a href="#">NRM2-617</a>	6" Round Regress Baffle Adjustable (1500lm only)
<a href="#">NRM2-619</a>	6" Round Regress Reflector Adjustable (1500lm only)



**Emergency:** Housing can be specified with connections for emergency battery installation. Requires top access. Must specify battery with remote test switch separately, [NEPK-07LEDUNV](#).

## LABELS AND LISTINGS

- cULus Listed for Damp Location w/ Feed Through (Wet Location when used with compatible reflector)
- [5-Year Limited Warranty](#)
- Meets or exceeds ASTM-283 Air-Tight Requirements
- FCC compliant



## PRODUCT IMAGES AND DIMENSIONS



## 6" Marquise II IC Air-Tight Double Wall New Construction Housing - Compatible with Marquise II Reflectors

Installation Type / Lumens / Wattage	Driver
NHMICD2-615 = IC / 1500lm / 18W	LE3 = 120V Input; Triac/ELV/0-10V dimming LE6 = 120-277V Input; 0-10V dimming
NHMICD2-620 = IC / 2000lm / 24W	LE6 = 120-277V Input; 0-10V dimming

## Optional Accessories

Description
NEPK-07LEDUNV = Remote Emergency Battery w/Test Switch

Example: **NHMICD2-620LE6** = 6" Marquise II IC Air-Tight Double Wall New Construction Housing, 2000lm / 24W LED, 120-277V Input