## PRODUCT DESCRIPTION

Line voltage BR/PAR Shroud fixture. Yoke provides full adjustment of light source for special aiming and dual tightening knob assure lock on angle position.

## FEATURES

- · Deep drawn steel socket cup housing for high strength and rigidity
- $\cdot$  Heat resistant Teflon coated wire lead
- $\cdot\,$  Low profile gimbal ring with minimal profile
- $\cdot$  Adjustable yoke for custom aiming
- $\cdot\,$  High-strength stainless steel electrical contacts
- $\cdot$  One or two circuit track capable
- Accepts LED lamps

#### CONSTRUCTION

Housing Socket Cup: 0.035" Deep drawn steel construction with simple, cylindrical design. All edges are softened for aesthetic appearance.

Gimbal Ring: 0.030" Baked enamel finished steel ring with dual brackets spot welded to socket cup enclosure.

Yoke: 0.085" Rigid steel "wishbone" yoke connects fixture housing to electrical contact head. Dual semi tubular rivets and friction washers provide secure hold for vertical angle.

#### ELECTRICAL SYSTEM

Socket: Porcelain jacketed aluminum screw thread medium-base socket

Wiring: Teflon coated wire lead connects socket and housing to electrical contact head. Teflon coating is durable and resists heat degradation from lamp and housing radiation.

Lamp: 250W BR40/PAR38 max. (not included)

#### **OPTIONAL ACCESSORIES**

NT-340: BR40/PAR38 Black Barn Door NT-343: BR40/PAR38 Black Louver (requires NT-340 or NT-346) NT-346: BR40/PAR38 Black Accessory Holder

### **ONE/TWO CIRCUIT CONVERSION**

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT- 2300 series two-circuit track.

#### LABELS AND LISTINGS

UL Listed



Type Project


\_\_\_\_\_

Catalog No.

# Notes

## PRODUCT IMAGES AND DIMENSIONS





Optional Accessories
Description
NT-340 = BR40/PAR38 Barn Door, Black NT-343 = BR40/PAR38 Louver, Black (Requires NT-340 or NT-346) NT-346 = BR40/PAR38 Accessory Holder, Black
-

Example: NTH-150B = BR/PAR38 Shroud, Black Finish, H-Style Adapter

NORA