

# NTL-207

MR16 Low Voltage Gimbal Ring Track Head

Lamp: 20W - 50W Halogen MR16

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

## PRODUCT DESCRIPTION

Low voltage die cast aluminum designer cube fixtures with MR16 light source. Yoke provides full adjustment of light source for special aiming and dual tightening knobs assure secure lock on angle position.

## FEATURES

- Die cast aluminum provides superior strength and rigidity
- Low profile, aesthetic design
- Adjustable yoke for custom aiming
- Clear shield included with fixture
- High-strength stainless steel electrical contacts
- One or two circuit track capable

## CONSTRUCTION

**Contact Head Assembly:** Three .030 stainless steel contacts mounted in high heat rated plastic housing.

**Gimbal Ring:** .030 Baked enamel finished steel ring. High-tension stainless steel spring secures MR16 light source.

**"L" Bracket Mount:** 0.85 Rigid steel yoke connects fixture housing to electrical contact head. Dual plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provides secure angle position.

## ELECTRICAL

**Voltage:** 120V input

**Socket:** Porcelain socket for GU5.3 12V MR16 lamp

**Lamp:** 20W - 50W Halogen MR16 (not included). **Note:** Do not use provided glass lens when MR16 lamp already comes with lens.

## ONE/TWO CIRCUIT CONVERSION

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

## OPTIONAL ACCESSORIES


**NM-100R/MR16:** Red MR16 Filter

## LABELS AND LISTINGS

UL Listed



## PRODUCT IMAGES AND DIMENSIONS



## MR16 Low Voltage Gimbal Ring Track Head

Catalog No. \_\_\_\_\_

**NTL-207BZ** = Bronze

## Optional Accessories

Description \_\_\_\_\_

**NM-100R/MR16** = Red MR16 Filter

Example: **NTL-207BZ** = MR16 Low Voltage Gimbal Ring Track Head, Bronze Finish