

NTM-615

6" Sloped Metal Baffle Trim

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.040 metal baffle with deep grooves to reduce aperture glare, and white flange. Non-reflective painted finishes.

Mounting: Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22). Accommodates slope ceilings with a 2/12 - 6/12 pitch to provide straight downlighting.

COMPATIBLE LAMP / HOUSINGS

Sloped Line Voltage:

- 75W BR30/PAR30 Maximum ([NHIC-9260AT](#); [NHRIC-9260AT](#))
- 100W BR40/PAR38 Maximum ([NHIC-926DWQAT](#))

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.




PRODUCT IMAGES & DIMENSIONS



NTM-615B

NTM-615W



6" Sloped Metal Baffle Trim

Catalog No. _____

NTM-615B: Black Metal Baffle with White Flange

NTM-615W: White Metal Baffle with White Flange

Compatible Housings

Sloped Line Voltage

Catalog No. _____

NHIC-9260AT = IC Air-Tight New Construction Sloped / 75W max.

NHRIC-9260AT = IC Air-Tight Remodel Sloped Sloped / 75W max.

NHIC-926DWQAT = IC Air-Tight Double Wall Sloped / 100W max.

Example: **NTM-615B** = 6" Sloped Black Metal Baffle with White Flange