



NEW PRODUCT ANNOUNCEMENT


M4 SERIES

4" LED Recessed (No Housing Required!)

M4 recessed downlights do not require any housings, which makes installation easy. Simply cut the ceiling, wire the junction box and insert the luminaire in the ceiling cavity. IC Air-Tight rated luminaires are available in round or square apertures in a variety of styles in matte powder white or matte black finish. A range of accessories allows customization to desired appearance.

FEATURES

- No housing required - IC Air-Tight rated
- Easy installation for remodel or new construction applications
- Customize each luminaire with optional square trim accessory
- Variety of reflector, square baffle, elbow or gimbal options
- Quick disconnect cables allow for extended lengths from LED drivers
- Delivering up to 1100lm in 2700K or 3000K at 90+ CRI
- Triac or ELV dimming
- 5-year limited warranty
- ENERGY STAR certified
- cETLus Listed for Wet or Damp Location
- Certified to the high efficacy requirements of California Title 24 JA8-2019

**NM4-R470 / NM4-SET**
Elbow w/ Square Trim**NM4-R470**
4" Round Elbow**NM4-RDC / NM4-SDT**
Downlight w/ Square Trim**NM4-RDC**
4" Round Downlight**NM4-RG**
4" Round Gimbal

M4 4" LED RECESSED

TRIM TYPE / LUMENS	CCT / CRI	FINISH
NM4-RDC Round Downlight / 1100lm	27 2700K / 90 CRI	BB Matte Black
NM4-RG Round Gimbal / 950lm	30 3000K / 90 CRI	MPW Matte Powder White
NM4-R470 Round Elbow / 950lm		

Ex: **NM4-RDC30MPW** - 4" M4 Round LED Downlight, 1000lm / 3000K, Matte Powder White

M4 ACCESSORIES

DESCRIPTION	FINISH
NM4-SDT Square Trim for NM4-RDC	B Matte Black
NM4-SET Square Trim for NM4-R470	MPW Matte Powder White
NF-R246 Universal New Construction Frame-In for NM4-RG & NM4-R470	
NF-R375 New Construction Frame-In for NM4-RDC	
NM2-EW-4 4' Quick Connect Linkable Extension Cable	
NM2-EW-10 10' Quick Connect Linkable Extension Cable	





M4 LED DOWNLIGHTS



4" M4 LED Round Downlight

NM4-RDC

Input Voltage: 120V
 Lumens / Wattage: 1100lm / 15W
 Color Temperature: 2700K or 3000K
 Finish: Matte Black or Matte Powder White
 Dimming: Triac or ELV
 Listing: Wet Location



4" M4 LED Round Adjustable Gimbal

NM4-RG

Input Voltage: 120V
 Lumens / Wattage: 950lm / 12W
 Color Temperature: 2700K or 3000K
 Finish: Matte Black or Matte Powder White
 Dimming: Triac or ELV
 Listing: Wet Location



4" M4 LED Round Adjustable Elbow

NM4-R470

Input Voltage: 120V
 Lumens / Wattage: 950lm / 12W
 Color Temperature: 2700K or 3000K
 Finish: Matte Black or Matte Powder White
 Dimming: Triac or ELV
 Listing: Damp


Accessories



New Construction Frame-In



Quick Connect Extension Cables



Square Baffle Trim for NM4-RDC



Square Trim for NM4-R470

NF-R246 for NM4-RG & NM4-R470
NF-R375 for NM4-RDC only

NM2-EW-4 4' Extension Cable
NM2-EW-10 10' Extension Cable

NM4-SDTB Black
NM4-SDTMPW Matte Powder White
NM4-SETB Black
NM4-SETMPW Matte Powder White

Photometrics

Part Number: NM4-RDC30MPW
Beam Spread: 37° Narrow Flood
Lumens: 1177lm
Wattage: 14.41W
Efficacy: 82lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180°): 0.62
Spacing Criteria (90°-270°): 0.6

Part Number: NM4-RG30MPW
Beam Spread: 28° Narrow Flood
Lumens: 958lm
Wattage: 11.67W
Efficacy: 82lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180°): 0.46
Spacing Criteria (90°-270°): 0.46

Part Number: NM4-R47030MPW
Beam Spread: 40° Narrow Flood
Lumens: 970lm
Wattage: 11.56W
Efficacy: 84lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180°): 0.66
Spacing Criteria (90°-270°): 0.66

Illuminance at a Distance		
Distance from Luminaire	FC at Nadir	Beam Diameter
4'	158fc	2'-8"
6'	70.4fc	4'
8'	39.6fc	5'-5"
10'	25.3fc	6'-8"
12'	17.6fc	8'-1"

Illuminance at a Distance		
Distance from Luminaire	FC at Nadir	Beam Diameter
4'	206fc	1'-11"
6'	91.7fc	2'-11"
8'	51.6fc	3'-10"
10'	33fc	4'-10"
12'	22.9fc	5'-8"

Illuminance at a Distance		
Distance from Luminaire	FC at Nadir	Beam Diameter
4'	103fc	2'-11"
6'	45.9fc	4'-5"
8'	25.8fc	5'-11"
10'	16.5fc	7'-4"
12'	11.5fc	8'-10"