

# Installation Instructions

NIO-4RTFA

## 4" Round Flange Accessory

READ PRIOR TO ATTEMPTING INSTALLATION  
ALWAYS TURN OFF MAIN POWER BEFORE INSTALLATION  
INSTALLATION SHOULD BE CARRIED OUT BY YOUR LOCAL ELECTRICIAN

**⚠ IMPORTANT** - This equipment is intended to be installed only by qualified personnel. The installation must be made in accordance with the current edition of the National Electrical Code and all applicable state and local building codes. The final installation must be approved by the appropriate, qualified electrical/building inspector(s). Improper installation may result in a fire or electrical hazard. Be sure the electrical power to the circuit has been disconnected before installing this electrical system.

**⚠ IMPORTANT** - Cet équipement est destiné à être installé uniquement par du personnel qualifié. L'installation doit être faite conformément à l'édition actuelle du Code national de l'électricité et à tous les codes de construction locaux et nationaux applicables. L'installation finale doit être approuvée par un ou plusieurs inspecteurs qualifiés en électricité / bâtiment. Une installation incorrecte peut entraîner un incendie ou un risque électrique. Assurez-vous que l'alimentation électrique du circuit a été déconnectée avant d'installer ce système électrique.

COMPATIBLE TRIMS	DESCRIPTION
NIO-4RTLND	4" Iolite Round Trimless Downlight
NIO-4RTSLA	4" Iolite Round Trimless Adjustable Slot

### INSTALLATION INSTRUCTIONS

**⚠ IMPORTANT:** Connector is not intended to support weight of the fixture. Please support fixture at all times.

1. Make sure power is off.
2. Snap flange accessory to trim. (Figure 1)
3. Connect orange male connector to female connector of compatible housing listed on the correlation label. (Figure 2)
4. Squeeze friction blades on flange accessory, route wires into the housing and push trim flush against ceiling. (Figure 3)
5. Turn power back on.

Figure 1




Figure 2




Figure 3

