

M-WAVE SERIES

Adjustable Can-less Downlights 90° Tilt & 350° Rotation (No Housing Required!)

M-Wave can-less luminaires offer the most versatility for aiming without any housing needed! IC Air-Tight rated luminaires extend up to 90° from surface and rotate 350°, illuminating any direction needed. M-Wave downlights appear as puck lights, up to 1-3/8" off the surface when flush and delivering over 1250 lumens in 2700K or 3000K.

FEATURES

- No housing required and includes pre-wired junction box
- Quick disconnect allows for easy installation
- IC Air-Tight rated
- Two sizes and outputs (750lm or 1250lm)
- Available in matte black or matte powder white finish
- Dedicated CCT (2700K or 3000K) at 90+ CRI
- 120V input; Triac or ELV dimming
- Narrow flood optic installed
- Optional field changeable optics available
- cULus Listed for Wet Location
- ENERGY STAR certified
- Certified to the high efficacy requirements of California Title 24 JA8-2022



M-WAVE ADJUSTABLE CAN-LESS LED DOWNLIGHTS

SIZE / LUMENS / WATTAGE	CCT	FINISH
NMW-2 2" M-Wave / 750lm / 9W	27 2700K	B Matte Black
NMW-4 4" M-Wave / 1250lm / 14W	30 3000K	MPW Matte Powder White

Ex: **NMW-230B** - 2" M-Wave Adjustable LED Downlight, 750lm / 9W, 3000K, Matte Black

M-WAVE ACCESSORIES

DESCRIPTION
NF-R124 New Construction Frame-In for NMW-4
NCA-EW-4 4' Extension Cable
NCA-EW-10 10' Extension Cable
NMWA-20PTSP Narrow Spot Optic for NMW-2
NMWA-20PTNFL Spot Optic for NMW-2
NMWA-40PTSP Narrow Spot Optic for NMW-4
NMWA-40PTNFL Spot Optic for NMW-4

