

FLAT SERIES

4" & 6" Canless Wafer Downlights Non-Metallic Trim & Selectable CCT

FLIN wafer can-less LED downlights feature a non-metallic trim for corrosive environments. Can-less downlights are easy to install in new construction or remodel applications. Tunable white luminaires include an integral tunable CCT switch located on the junction box of each luminaire with a quick connect that allows for easy disconnect and mounting in the ceiling. The regressed lens with sharp baffle cuts reduce aperture brightness.

FEATURES

- Two sizes and outputs (700lm or 1050lm)
- Dead front (non-metallic) trim for corrosive environments
- No housing required and includes pre-wired junction box
- Quick disconnect allows for easy installation
- Junction box includes selectable color temperature switch
- Only 3/8" tall, ideal for shallow plenums
- IC Air-Tight rated
- Five color temperatures in each fixture (2700K, 3000K, 3500K, 4000K or 5000K)
- 120V input with Triac or ELV dimming
- cETLus Listed for Wet locations
- ENERGY STAR certified
- Can be used to comply with 2022 Title 24 Part 6 high efficacy requirements



FLAT WAFER CAN-LESS LED DOWNLIGHTS

DESCRIPTION

- [NFLAT-R4TWMPW](#) 4" FLAT Downlight, 700lm / 10W, Selectable CCT
- [NFLAT-R6TWMPW](#) 6" FLAT Downlight, 1050lm / 13.5W, Selectable CCT

OPTIONAL ACCESSORIES

DESCRIPTION


- [NF-R246](#) Universal New Construction Frame-In
- [NFC-R430](#) New Construction Frame-In with Collar for NFLAT-R4TWMPW
- [NFP-R413](#) New Construction Plate for NFLAT-R4TWMPW
- [NFP-R613](#) New Construction Plate for NFLAT-R6TWMPW
- [NEFLINTW-EW-4](#) 4' Extension Cable
- [NEFLINTW-EW-20](#) 20' Extension Cable



NFLAT-R4TWMPW
4" FLAT
700lm



Selectable CCT
Five position switch
27K / 30K / 35K / 40K / 50K



NFLAT-R6TWMPW
6" FLAT
1050lm

