

# NOXAC-432TW

4" AC Onyx LED Retrofit Baffle with Selectable CCT

Source: 11.5W

900lm

Type

Project

Catalog No.

Notes

## PRODUCT DESCRIPTION

4" AC Onyx Retrofit Series requires no driver and allow for a sleek design. Spun aluminum construction provides clean sharp edges and is suitable for use with most 4" recessed housings. Deep regressed optics and round aperture deliver even and glare-free illumination.

## FEATURES

- Over 900 delivered lumens
- Five color temperatures in each fixture (2700K / 3000K / 3500K / 4000K / 5000K)
- Dimmable AC LED
- Includes medium base socket adapter for easy retrofitting in 4" recessed housings
- Quick connector is compatible with dedicated LED housings
- 5-year limited warranty
- Classified for wet locations
- ENERGY STAR certified

## SPECIFICATION

**Reflector:** One piece, spun aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

**Mounting:** Two steel, spring mounting blades allow for easy and secure mounting in most 4" housings.

**Retrofit:** Luminaires include a medium base screw-socket adapter (NRA-21ISM) for retrofitting into medium base downlight housings. Intended to be used as a LED lamp replacement. GU24 socket adapter (NRA-212SM) is available.

## ELECTRICAL

**Voltage:** 120VAC

**Lumens / Wattage:** 900lm / 11.5W

**Color Temperature:** Selectable CCT: 2700K / 3000K / 3500K / 4000K / 5000K (Note: Preset to 3000K)

**Color Rendering Index:** 90+ CRI

**Operating Temperature:** 0°C to 35°C ambient temperature

**Lifetime:** 50,000 hours @ L70

**Dimming:** Triac/ELV

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

## COMPATIBLE HOUSINGS

Onyx retrofits are compatible with most 4" IC and Non-IC housings by Nora and others.

### Fire Box

- NFJB-R4\* ICAT Junction Box
- NFBIC-4LMRATA\* IC Air-Tight Dedicated LED Firebox
- NFBIC-427LMRATA\* Shallow ICAT Dedicated LED Firebox
- NFBIC-4INCATA IC Air-Tight Line Voltage Firebox

### New Construction

- NHIC-4LMRAT\* IC Air-Tight Dedicated LED
- NHIC-4LMRAT/277\* ICAT Dedicated LED, 277V (includes step-down transformer)
- NHICCP-4LMRAT\* Chicago Plenum Dedicated LED
- NHIC-427LMRAT\* Shallow IC Air-Tight Dedicated LED
- NSIC-401QAT IC Air-Tight Line Voltage
- NS-401QAT Air-Tight Line Voltage
- NHIC-4G24AT IC Air-Tight GU24

### Remodel

- NHRIC-4LMRAT\* IC Air-Tight Dedicated LED
- NHRIC-427LMRAT\* Shallow IC Air-Tight Dedicated LED
- NSR-404QAT Air-Tight Line Voltage
- NSRIC-404QAT IC Air-Tight Line Voltage

\* Nora LED Dedicated housings are listed for use only with Nora LED Retrofits.

## ACCESSORIES

- NOX-4EYELIDW:** White round eyelid used to convert round reflector or baffle to half moon wall wash trim.
- NOX-4OR-W:** White round oversize ring used to cover ceiling cut-outs up to 5-7/8".

## LABELS AND LISTINGS

- cETLus classified for Wet Locations
- ENERGY STAR certified
- 5-Year Limited Warranty
- Meets ASTM-E283 Air-Tight requirements
- FCC compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2022



Performance Data		
Part Number	Lumens	CCT
NOXAC-432TWWW	816lm	2700K
NOXAC-432TWWW	857lm	3000K
NOXAC-432TWWW	914lm	3500K
NOXAC-432TWWW	919lm	4000K
NOXAC-432TWWW	915lm	5000K

## PRODUCT IMAGES AND DIMENSIONS





NOXAC-432TWWW  
White Finish



NOXAC-432TW / NOX-4EYELIDW  
White Eyelid



NOXAC-432TW / NOX-4OR-W  
White Oversize Ring



## 4" AC Onyx LED Retrofit Baffle with Selectable CCT

Finish

NOXAC-432TWWW = White Finish

## Optional Accessories

Description

- NOX-4EYELIDW = 4" Round White Eyelid
- NOX-4OR-W = 4" Round White Oversize Ring
- NRA-21ISM = Medium base screw-in socket (included w/ each)
- NRA-212SM = Socket adapter for use with GU24 housings

Example: NOXAC-432TWWW = 4" AC Onyx LED Round Baffle Reflector with Selectable CCT, White Baffle / White Flange