


# FIRE RATED CAN-LESS

## 2-Hour Certified & Listed Five Selectable CCT Switch 4" & 6" trims / up to 1550 lumens


Fire rated can-less downlights are tested and listed to UL 263, ASTM E119 & CAN/ULC S101 two-hour fire rating. Wafer design allows luminaires to be installed in shallow plenums and include a selectable five color temperature switch. Multi-piece construction provides an extra layer of protection to prevent the spread of fire above the ceiling within a two-hour rating.

### FEATURES

- cETLus Listed to Two-Hour Fire Rating, not only tested!
- Tested / Complies ≠ Listed (Others will not pass inspection!)
- IC Airtight rated (ASTM E283)
- No housing required and includes pre-wired junction box
- Two Sizes and Outputs (4" / 1200lm or 6" / 1550lm)
- Three Trim Types (Flat, Regressed, or Baffle)
- Selectable Color Temperature (2700K / 3000K / 3500K / 4000K / 5000K)
- 120V input; Phase dimming (Triac or ELV)
- Multi-piece construction provides two-hour fire barrier
- Shallow design for low clearance plenums
- 5-Year limited warranty
- cETLus Listed
- ENERGY STAR certified
- Certified to the high efficacy requirements of California Title 24




Five position sliding switch  
27K / 30K / 35K / 40K / 50K



NFRC-R4W1 (4")  
NFRC-R6W1 (6")  
Flat



NFRC-R4W3 (4")  
NFRC-R6W3 (6")  
Regressed



NFRC-R4W2 (4")  
NFRC-R6W2 (6")  
Baffle



### FIRE RATED CAN-LESS DOWNLIGHTS

PART NUMBER	DESCRIPTION
<a href="#">NFRC-R4W1TWMPW</a>	4" Flat / 1200lm / 12W
<a href="#">NFRC-R4W2TWMPW</a>	4" Baffle / 1200lm / 12W
<a href="#">NFRC-R4W3TWMPW</a>	4" Regressed / 1200lm / 12W
<a href="#">NFRC-R6W1TWMPW</a>	6" Flat / 1550lm / 15W
<a href="#">NFRC-R6W2TWMPW</a>	6" Baffle / 1500lm / 15W
<a href="#">NFRC-R6W3TWMPW</a>	6" Regressed / 1500lm / 15W
OPTIONAL ACCESSORIES	
<a href="#">NEPK-20LEDUNV</a>	20W Emergency LED Driver with Remote Test Switch
<a href="#">NF-R246</a>	Universal New Construction Frame-In for 4" & 6"
<a href="#">NFC-R430</a>	New Construction Frame-In for 4" only