

NH-260

6" Non-IC Line Voltage New Construction Housing

Source: 150W Max. (Varies by trim)

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

New construction housing for use where insulation can be kept 3" away from housing. The housing is labeled for use with Nora 6" line voltage trims and compatible with all LED retrofits.

FEATURES

- Internal thermal protection
- cULus listed for damp location and through branch circuit wiring
- Quick connect provided
- 24-1/2" Bar hangers with captive nails and alignment foot
- Accommodates 1-5/8" maximum ceiling thickness

CONSTRUCTION

Plastic Frame: High quality 0.032 steel die cut one piece frame.

Housing: 0.040 steel housing with riveted cap adjusts to maximum ceiling thickness of 1-5/8". Spring brackets accept torsion wing trim springs; slots on socket plate accept standard coil springs.

Minimum Clearance: Non-IC housings require a minimum clearance of 3" from thermal insulation and 1/2" from adjacent building components.

Socket: Galvanized steel socket plate adjusts inside housing for optimum light performance. Contains a single medium base socket. Protective cap included to protect socket interior during ceiling painting. Socket plate can be removed in the field to convert to a floating socket.

Bar Hangers: Two 13-3/4" to 24-1/2" adjustable bar hangers with captive nails are included on frame. Hanger bars have T-Bar slot and alignment feet. Bar hangers are parallel to junction box, but can be repositioned 90° perpendicular to junction box if desired. "L" Shaped bar hanger foot to align to bottom of construction joist. A T-Bar notch allows easy installation in a suspended ceiling.

Junction Box: Prewired 25 cubic inch 0.064" thick galvanized steel box with five 1/2", two 3/4" knockouts and snap on covers. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Through branch circuit wiring, (4-in, 4-out).

Romex Strain Relief: Junction box includes two Romex tabs with two slots at each tab for NM-cables of 12/2 to 14/2. The strain relief allows for easy installation and less materials.

Quick Connect Feature: Housing contains three UL approved quick connections that allow insertion of 1/4" stripped solid or tinned standard conductors to be inserted into the connector. Connectors are pre-attached to fixture power, common, and ground circuits.

Thermal Protector: Standard UL thermal protector rated for 90°C is affixed to inner top surface of housing.

ELECTRICAL

Input Voltage: 120V

Socket: Medium base

Lamp: Lamp type based on trim selection



Wattage: 150W max. (wattage varies based on trim selection)

LABELS AND LISTINGS

- cULus Listed for Damp Location w/ Feed Through (Wet Location when used with designated trims)
- NYC Approved: Calendar #43895



PRODUCT IMAGES & DIMENSIONS



6" Non-IC Line Voltage New Construction Housing

Housing Type

NH-260: 6" Non-IC Line Voltage New Construction Housing, Adjustable Socket Bracket

Example: **NH-260** = 6" Non-IC Line Voltage New Construction Housing, Adjustable Socket Bracket