

# NL-3345

## 3" Adjustable Slot Aperture

### FEATURES

**Trim:** Metal trim with 1-1/8" x 1-3/4" slot aperture that can rotate 358° horizontally. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Separate trim ring available in custom combination of ring finishes (consult factory).

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

### LAMP

#### Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

#### Low Voltage

**Important:** Do not use glass lens (provided) when already using lamp with glass cover  
50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series; NLR-305 Series)

### LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



Type

Project

Catalog No.

Notes

### Product Images and Dimensions



**NL-3345BZ**  
Bronze Trim



**NL-3345C**  
Chrome Ring



**NL-3345CO**  
Copper Ring




**NL-3345G**  
Gold Ring



**NL-3345N**  
Natural Metal Ring



**NL-3345W**  
White Ring



### 3" Adjustable Slot Aperture

Catalog No.

- NL-3345BZ** = Adjustable Slot Aperture, Bronze Trim
- NL-3345C** = Adjustable Slot Aperture, Chrome Trim
- NL-3345CO** = Adjustable Slot Aperture, Copper Trim
- NL-3345G** = Adjustable Slot Aperture, Gold Trim
- NL-3345N** = Adjustable Slot Aperture, Natural Metal Trim
- NL-3345W** = Adjustable Slot Aperture, White Trim

### Compatible Housings

#### Line Voltage

Catalog No.

- NH-350AT** = 3" Non-IC Air-Tight New Construction Housing / 50W max.
- NHIC-350AT** = 3" IC Air-Tight New Construction Housing / 50W max.
- NHR-354AT** = 3" Non-IC Air-Tight Remodel Housing / 50W max.

#### Low Voltage

Catalog No.

- NLIC-301AT/1EL** = 3" IC Air-Tight New Construction Housing / 50W max.
- NLIC-301QAT/20** = 3" IC Air-Tight New Construction Housing / 20W max.
- NLIC-301QAT/37** = 3" IC Air-Tight New Construction Housing / 37W max.
- NLIC-301QAT** = 3" IC Air-Tight New Construction Housing / 50W max.
- NL-301AT/1EL** = 3" Non-IC Air-Tight New Const. Housing / 50W max.
- NL-301QAT/20** = 3" Non-IC Air-Tight New Const. Housing / 20W max.
- NL-301QAT/37** = 3" Non-IC Air-Tight New Const. Housing / 37W max.
- NL-301QAT** = 3" Non-IC Air-Tight New Const. Housing / 50W max.
- NLR-304AT/1EL** = 3" Non-IC Air-Tight Remodel Housing / 50W max.
- NLR-304QAT/20** = 3" Non-IC Air-Tight Remodel Housing / 20W max.
- NLR-304QAT/37** = 3" Non-IC Air-Tight Remodel Housing / 37W max.
- NLR-304QAT** = 3" Non-IC Air-Tight Remodel Housing / 50W max.
- NLR-305AT/20** = 3" Non-IC Air-Tight Remodel Housing / 20W max.
- NLR-305AT/37** = 3" Non-IC Air-Tight Remodel Housing / 37W max.
- NLR-305AT** = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Example: **NL-3345BZ** = 3" Adjustable Slot Aperture, Bronze Trim