

# NL-3366

## 3" Front Loading Adjustable Gimbal

Type \_\_\_\_\_  
Project \_\_\_\_\_  
Catalog No. \_\_\_\_\_  
Notes \_\_\_\_\_

### FEATURES

**Trim:** Metal trim with adjustable ring can be adjusted up to 35°. Separate trim ring available in custom combination of ring finishes (consult factory).

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE HOUSINGS

Compatible with Low Voltage housings. See individual specification sheets for more information.

### LAMP

#### Low Voltage

**Important:** Do not use glass lens (provided) when already using lamp with glass cover  
50W 12V MR16 (NL-301 Series; NLIC-301 Series)

### LABELS AND LISTINGS


cULus Listed for Damp Location when used with compatible housing.



### Product Images and Dimensions



**NL-3366N**  
Natural Metal Trim



## 3" Front Loading Adjustable Gimbal

Catalog No. \_\_\_\_\_

**NL-3366N** = 3" Front Loading Adjustable Gimbal, Natural Metal Finish

## Compatible Housings

### Low Voltage

Catalog No. \_\_\_\_\_

- NLIC-301AT/1EL** = 3" IC Air-Tight New Construction Housing / 50W max.
- NLIC-301QAT/20** = 3" IC Air-Tight New Construction Housing / 20W max.
- NLIC-301QAT/37** = 3" IC Air-Tight New Construction Housing / 37W max.
- NLIC-301QAT** = 3" IC Air-Tight New Construction Housing / 50W max.
- NL-301AT/1EL** = 3" Non-IC Air-Tight New Const. Housing / 50W max.
- NL-301QAT/20** = 3" Non-IC Air-Tight New Const. Housing / 20W max.
- NL-301QAT/37** = 3" Non-IC Air-Tight New Const. Housing / 37W max.
- NL-301QAT** = 3" Non-IC Air-Tight New Const. Housing / 50W max.

Example: **NL-3366N** = 3" Front Loading Adjustable Gimbal, Natural Metal Finish