

# NL-413 / NL-414 / NL-416 / NL-453

## 4" Round Adjustable Reflector

Type

Project

Catalog No.

Notes

### FEATURES

**Trim:** Precision spun 0.050 aluminum high grade reflector. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

### LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



### COMPATIBLE LAMP / HOUSINGS

#### Low Voltage:


20W MR16 max. (NL-401QAT/20; NLIC-401QSAT/20; NLR-404QAT/20; NLR-405AT/20; NLIC-402SAT/20; NL-402S/20; NLR-403S/20)  
 37W MR16 max. (NL-401QAT/37; NLIC-401QSAT/37; NLR-404QAT/37; NLR-405AT/37; NLIC-402QSAT/37; NL-402S/37; NLR-403S/37)  
 50W MR16 max. (NLIC-401AT/1EL; NLIC-401AT/2EL; NLIC-401QSAT; NL-401AT/1EL; NL-401QAT; NLR-404AT/1EL; NLR-404AT/2EL; NLR-404QAT; NLR-405AT; NLIC-402AT/1EL; NLIC-402QSAT; NL-402S/1EL; NL-402S; NLR-403S/1EL; NLR-403S)  
 75W MR16 max. (NL-401/75/1EL; NLR-404/75/1EL; NLR-404/75/2EL; NLR-404/75)

#### Line Voltage:

20W MR16 max. (NSEIC-407AT/20; NSERIC-407AT/20)  
 25W MR16 max. (NFBIC-401AT/25A)  
 50W MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

**IMPORTANT: DO NOT USE GLASS LENS WHEN ALREADY USING LAMP W/ GLASS COVER**

### Product Dimensions



### Compatible Housings

Catalog No.

#### Low Voltage

**NLIC-401QSAT/20** = ICAT New Construction / 120V Magnetic / 20W max.  
**NLIC-401QSAT/37** = ICAT New Construction / 120V Magnetic / 37W max.  
**NLIC-401QSAT** = ICAT New Construction / 120V Magnetic / 50W max.  
**NLIC-401AT/1EL** = ICAT New Construction / 120V Electronic / 50W max.  
**NLIC-401AT/2EL** = ICAT New Construction / 120V Electronic / 50W max.  
**NL-401QAT/20** = Non-IC AT New Construction / 120V Magnetic / 20W max.  
**NL-401QAT/37** = Non-IC AT New Construction / 120V Magnetic / 37W max.  
**NL-401QAT** = Non-IC AT New Construction / 120V Magnetic / 50W max.  
**NL-401AT/1EL** = Non-IC AT New Construction / 120V Electronic / 50W max.  
**NL-401/75/1EL** = Non-IC New Construction / 120V Electronic / 75W max.  
**NLIC-402QSAT/20** = ICAT Shallow New Construction / 120V Magnetic / 20W max.  
**NLIC-402QSAT/37** = ICAT Shallow New Construction / 120V Magnetic / 37W max.  
**NLIC-402QSAT** = ICAT Shallow New Construction / 120V Magnetic / 50W max.  
**NLIC-402AT/1EL** = ICAT Shallow New Construction / 120V Electronic / 50W max.  
**NL-402S/20** = Non-IC Shallow New Construction / 120V Magnetic / 20W max.  
**NL-402S/37** = Non-IC Shallow New Construction / 120V Magnetic / 37W max.  
**NL-402S** = Non-IC Shallow New Construction / 120V Magnetic / 50W max.  
**NL-402S/1EL** = Non-IC Shallow New Construction / 120V Electronic / 50W max.  
**NLR-403S/20** = Non-IC Shallow Remodel / 120V Magnetic / 20W max.  
**NLR-403S/37** = Non-IC Shallow Remodel / 120V Magnetic / 37W max.  
**NLR-403S** = Non-IC Shallow Remodel / 120V Magnetic / 50W max.  
**NLR-403S/1EL** = Non-IC Shallow Remodel / 120V Electronic / 50W max.  
**NLR-404QAT/20** = Non-IC AT Remodel / 120V Magnetic / 20W max.  
**NLR-404QAT/37** = Non-IC AT Remodel / 120V Magnetic / 37W max.  
**NLR-404QAT** = Non-IC AT Remodel / 120V Magnetic / 50W max.  
**NLR-404/75** = Non-IC Remodel / 120V Magnetic / 75W max.  
**NLR-404AT/1EL** = Non-IC AT Remodel / 120V Electronic / 50W max.  
**NLR-404AT/2EL** = Non-IC AT Remodel / 277V Electronic / 50W max.  
**NLR-404/75/1EL** = Non-IC Remodel / 120V Electronic / 75W max.  
**NLR-404/75/2EL** = Non-IC Remodel / 277V Electronic / 75W max.  
**NLR-405AT/20** = Non-IC AT Remodel / No Transformer / 20W max.  
**NLR-405AT/37** = Non-IC AT Remodel / No Transformer / 37W max.  
**NLR-405AT** = Non-IC AT Remodel / No Transformer / 50W max.

#### Line Voltage

**NSEIC-407AT/20** = ICAT LED New Construction / 20W  
**NSERIC-407AT/20** = ICAT LED Remodel / 20W  
**NFBIC-401AT/25A** = Fire Rated IC Air-Tight New Construction / 25W  
**NSLIC-401AT/10** = ICAT New Construction / 50W  
**NSL-401AT/10** = Non-IC Air-Tight New Construction / 50W  
**NSLR-404AT/10** = Non-IC Air-Tight Remodel / 50W

### Product Images



**NL-413**  
Specular Black Reflector  
White Trim



**NL-414**  
Specular Clear Reflector  
White Trim



**NL-414HZ**  
Haze Reflector  
White Trim



**NL-416**  
Specular White Reflector  
White Trim



**NL-453**  
Copper Reflector  
Copper Trim



**NL-453BZ**  
Bronze Reflector  
Bronze Trim

### 4" Round Adjustable Reflector

Catalog No.

**NL-413** = Specular Black Reflector with White Metal Trim  
**NL-414** = Specular Clear Reflector with White Metal Trim  
**NL-414HZ** = Haze Reflector with White Metal Trim  
**NL-416** = White Reflector with White Metal Trim  
**NL-453** = Copper Reflector with Copper Metal Trim  
**NL-453BZ** = Bronze Reflector with Bronze Metal Trim

Example: **NL-414HZ** = 4" Round Haze Reflector with White Metal Trim