

# NL-418

## 4" Adjustable Eyeball with Baffle

Type

Project

Catalog No.

Notes

### FEATURES

**Trim:** Metal trim with adjustable eyeball can be rotated 358° horizontally and 35° vertically. Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare. Gimbal ring allows lamp to be mounted on top of the trim. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

### COMPATIBLE LAMP / HOUSINGS

#### Low Voltage:

20W MR16 max. (NL-401QAT/20; NLIC-401QSAT/20; NLR-404QAT/20; NLR-405AT/20; NLIC-402SAT/20; NL-402S/20; NLR-403S/20)

37W MR16 max. (NL-401QAT/37; NLIC-401QSAT/37; NLR-404QAT/37; NLR-405AT/37; NLIC-402QSAT/37; NL-402S/37; NLR-403S/37)

50W MR16 max. (NLIC-401AT/1EL; NLIC-401AT/2EL; NLIC-401QSAT; NL-401AT/1EL; NL-401AT/2EL; NL-401QAT; NLR-404AT/1EL; NLR-404AT/2EL; NLR-404QAT; NLR-405AT; NLIC-402AT/1EL; NLIC-402QSAT; NL-402S/1EL; NL-402S; NLR-403S/1EL; NLR-403S)

75W MR16 max. (NL-401/75/1EL; NL-401/75/2EL; NL-401/75; NLR-404/75/1EL; NLR-404/75/2EL; NLR-404/75)

#### Line Voltage:

20W MR16 max. (NSEIC-407AT/20; NSERIC-407AT/20)

25W MR16 max. (NFBIC-401AT/25A)

50W MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

### LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



### Product Images



**NL-418N**  
Natural Metal Baffle  
Natural Metal Trim



**NL-418WB**  
Black Baffle  
White Trim



**NL-418WW**  
White Baffle  
White Trim

### 4" Adjustable Eyeball with Baffle


Catalog No.

**NL-418N** = Natural Metal Baffle with Natural Metal Trim

**NL-418WB** = Black Baffle with White Trim

**NL-418WW** = White Baffle with White Trim

### Product Dimensions



### Compatible Housings

Catalog No.

#### Low Voltage

**NLIC-401QSAT/20** = ICAT New Construction / 120V Magnetic / 20W

**NLIC-401QSAT/37** = ICAT New Construction / 120V Magnetic / 37W

**NLIC-401QSAT** = ICAT New Construction / 120V Magnetic / 50W

**NLIC-401AT/1EL** = ICAT New Construction / 120V Electronic / 50W

**NLIC-401AT/2EL** = ICAT New Construction / 120V Electronic / 50W

**NL-401QAT/20** = Non-IC AT New Construction / 120V Magnetic / 20W

**NL-401QAT/37** = Non-IC AT New Construction / 120V Magnetic / 37W

**NL-401QAT** = Non-IC AT New Construction / 120V Magnetic / 50W

**NL-401/75** = Non-IC New Const. / 120V Magnetic / 75W

**NL-401AT/1EL** = Non-IC AT New Construction / 120V Electronic / 50W

**NL-401AT/2EL** = Non-IC AT New Construction / 277V Electronic / 50W

**NL-401/75/1EL** = Non-IC New Construction / 120V Electronic / 75W

**NL-401/75/2EL** = Non-IC New Construction / 277V Electronic / 75W

**NLIC-402QSAT/20** = ICAT Shallow New Construction / 120V Magnetic / 20W

**NLIC-402QSAT/37** = ICAT Shallow New Construction / 120V Magnetic / 37W

**NLIC-402QSAT** = ICAT Shallow New Construction / 120V Magnetic / 50W

**NLIC-402AT/1EL** = ICAT Shallow New Construction / 120V Electronic / 50W

**NL-402S/20** = Non-IC Shallow New Construction / 120V Magnetic / 20W

**NL-402S/37** = Non-IC Shallow New Construction / 120V Magnetic / 37W

**NL-402S** = Non-IC Shallow New Construction / 120V Magnetic / 50W

**NL-402S/1EL** = Non-IC Shallow New Construction / 120V Electronic / 50W

**NLR-403S/20** = Non-IC Shallow Remodel / 120V Magnetic / 20W

**NLR-403S/37** = Non-IC Shallow Remodel / 120V Magnetic / 37W

**NLR-403S** = Non-IC Shallow Remodel / 120V Magnetic / 50W

**NLR-403S/1EL** = Non-IC Shallow Remodel / 120V Electronic / 50W

**NLR-404QAT/20** = Non-IC AT Remodel / 120V Magnetic / 20W

**NLR-404QAT/37** = Non-IC AT Remodel / 120V Magnetic / 37W

**NLR-404QAT** = Non-IC AT Remodel / 120V Magnetic / 50W

**NLR-404/75** = Non-IC Remodel / 120V Magnetic / 75W

**NLR-404AT/1EL** = Non-IC AT Remodel / 120V Electronic / 50W

**NLR-404AT/2EL** = Non-IC AT Remodel / 277V Electronic / 50W

**NLR-404/75/1EL** = Non-IC Remodel / 120V Electronic / 75W

**NLR-404/75/2EL** = Non-IC Remodel / 277V Electronic / 75W

**NLR-405AT/20** = Non-IC AT Remodel / No Transformer / 20W

**NLR-405AT/37** = Non-IC AT Remodel / No Transformer / 37W

**NLR-405AT** = Non-IC AT Remodel / No Transformer / 50W

Example: **NL-418WB** = Adjustable White Elbow with Black Baffle