


NL-448 / NL-449
Adjustable Wall Wash with Baffle

TRIM DIMENSIONS



Trim OD: 5"
 Height: 2-3/8"

FEATURES

Trim
 Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare with half moon. Non-reflective painted finishes. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

Mounting
 Trim includes three trim clips that securely mount trim in housing.

Compatible Housings
 Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

Lamp
Line Voltage
 50W 120V MR16 GU10 Max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)
Low Voltage
 20W-75W 12V MR16 (NL-401 Series; NL-402 Series; NLIC-401 Series; NLIC-402 Series; NLR-403 Series; NLR-404 Series; NLR-405 Series)

Labels and Listings
 cULus Listed for Damp Location when used with compatible housing.

IMPORTANT:
 DO NOT USE GLASS LENS WHEN ALREADY USING LAMP w/ GLASS COVER

Adjustable Wall Wash with Baffle

- NL-448: White Adjustable Wall Wash with Black Baffle and White Ring
- NL-448BZ: Bronze Adjustable Wall Wash with Bronze Baffle and Bronze Ring
- NL-448CO: Copper Adjustable Wall Wash with Copper Baffle and Copper Ring
- NL-448N: Natural Metal Adjustable Wall Wash with Natural Metal Baffle and Natural Metal Ring
- NL-449: White Adjustable Wall Wash with White Baffle and White Ring

Type
Project
Catalog No.
Lamp/Wattage

Compatible Housings

LINE VOLTAGE			
Item Number	Installation Type	Lamp	Dimensions
NSL-401AT/10	Non-IC Air-Tight New Const.	50W MR16	W: 5-5/8" L: 8-1/2" H: 5-3/4"
NSLIC-401AT/10	IC Air-Tight New Construction	50W MR16	W: 8" L: 12-5/8" H: 8"
NSLR-404AT/10	Non-IC Air-Tight Remodel	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
LOW VOLTAGE			
NL-401QAT/20	Non-IC AT New Const., Mag.	20W MR16	W: 6" L: 9" H: 5-1/2"
NL-401QAT/37	Non-IC AT New Const., Mag.	37W MR16	W: 6" L: 9" H: 5-1/2"
NL-401QAT	Non-IC AT New Const., Mag.	50W MR16	W: 6" L: 9" H: 5-1/2"
NL-401/50/277AT	Non-IC AT New Const., Mag.	50W MR16	W: 6" L: 9" H: 5-1/2"
NL-401AT/1EL	Non-IC AT New Const., Elec.	50W MR16	W: 6" L: 9" H: 5-1/2"
NL-401AT/2EL	Non-IC AT New Const., Elec.	50W MR16	W: 6" L: 9" H: 5-1/2"
NL-401/75	Non-IC AT New Const., Mag.	75W MR16	W: 7" L: 11-1/2" H: 6-3/8"
NL-401/75/277	Non-IC AT New Const., Mag.	75W MR16	W: 7" L: 11-1/2" H: 6-3/8"
NL-401/75/1EL	Non-IC AT New Const., Elec.	75W MR16	W: 7" L: 11-1/2" H: 6-3/8"
NL-401/75/2EL	Non-IC AT New Const., Elec.	75W MR16	W: 7" L: 11-1/2" H: 6-3/8"
NL-402S/20	Non-IC Shallow New Con., Mag.	20W MR16	W: 6" L: 8-1/2" H: 3-1/2"
NL-402S/37	Non-IC Shallow New Con., Mag.	37W MR16	W: 6" L: 8-1/2" H: 3-1/2"
NL-402S	Non-IC Shallow New Con., Mag.	50W MR16	W: 6" L: 8-1/2" H: 3-1/2"
NL-402S/1EL	Non-IC Shallow New Con., Elec.	50W MR16	W: 6" L: 8-1/2" H: 3-1/2"
NLIC-401QSAT/20	IC Air-Tight New Const., Mag.	20W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-401QSAT/37	IC Air-Tight New Const., Mag.	37W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-401QSAT	IC Air-Tight New Const., Mag.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-401AT/277V	IC Air-Tight New Const., Mag.	50W MR16	W: 10-3/4" L: 17-3/4" H: 7-1/2"
NLIC-401AT/1EL	IC Air-Tight New Const., Elec.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-401AT/2EL	IC Air-Tight New Const., Elec.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-402QSAT/20	IC Air-Tight Shallow NC, Mag.	20W MR16	W: 13-1/8" L: 14" H: 5-3/8"
NLIC-402QSAT/37	IC Air-Tight Shallow NC, Mag.	37W MR16	W: 13-1/8" L: 14" H: 5-3/8"
NLIC-402QSAT	IC Air-Tight Shallow NC, Mag.	50W MR16	W: 13-1/8" L: 14" H: 5-3/8"
NLIC-402AT/1EL	IC Air-Tight Shallow NC, Elec.	50W MR16	W: 13-1/8" L: 14" H: 5-3/8"
NLR-403S/20	Non-IC Shallow Remodel, Mag.	20W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
NLR-403S/37	Non-IC Shallow Remodel, Mag.	37W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
NLR-403S	Non-IC Shallow Remodel, Mag.	50W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
NLR-403S/1EL	Non-IC Shallow Remodel, Elec.	50W MR16	W: 4-7/8" L: 11-3/4" H: 3-1/2"
NLR-404QAT/20	Non-IC Air-Tight Remodel, Mag.	20W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404QAT/37	Non-IC Air-Tight Remodel, Mag.	37W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404QAT	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404/50/277	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404AT/1EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404AT/2EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404AT/75	Non-IC Remodel, Magnetic	75W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
NLR-404/75/277	Non-IC Remodel, Magnetic	75W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
NLR-404/75/1EL	Non-IC Remodel, Electronic	75W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
NLR-404/75/2EL	Non-IC Remodel, Electronic	75W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
NLR-405AT/20	Non-IC Air-Tight Remodel	20W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"
NLR-405AT/37	Non-IC Air-Tight Remodel	37W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"
NLR-405AT	Non-IC Air-Tight Remodel	50W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"