

NL-465

4" Round Surface Adjustable

Type

Project

Catalog No.

Notes

FEATURES

Trim: Metal trim with adjustable ring can be adjusted up to 43°. Adjustable ring allows lamp to be mounted on top of the trim. Trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

COMPATIBLE LAMP / HOUSINGS

Low Voltage:

50W MR16 max. (NLIC-401AT/1EL; NLIC-401AT/2EL; NLIC-401QSAT; NL-401AT/1EL; NL-401QAT; NLR-404AT/1EL; NLR-404AT/2EL; NLR-404QAT; NLIC-402AT/1EL; NLIC-402QSAT; NL-402S/1EL; NL-402S; NLR-403S/1EL; NLR-403S)
75W MR16 max. (NLR-404/75/2EL)

Line Voltage:

20W MR16 max. (NSEIC-407AT/20; NSERIC-407AT/20)
25W MR16 max. (NFBIC-401AT/25A)
50W MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

OPTIONAL ACCESSORY

NT-350B: Black Snoot


IMPORTANT: DO NOT USE GLASS LENS WHEN ALREADY USING LAMP W/ GLASS COVER

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



Product Dimensions



Compatible Housings

Catalog No.

Low Voltage

- NLIC-401QSAT = ICAT New Construction / 120V Magnetic / 50W
- NLIC-401AT/1EL = ICAT New Construction / 120V Electronic / 50W
- NLIC-401AT/2EL = ICAT New Construction / 120V Electronic / 50W
- NL-401QAT/20 = Non-IC AT New Construction / 120V Magnetic / 20W
- NL-401QAT = Non-IC AT New Construction / 120V Magnetic / 50W
- NL-401AT/1EL = Non-IC AT New Construction / 120V Electronic / 50W
- NLIC-402QSAT = ICAT Shallow New Construction / 120V Magnetic / 50W
- NLIC-402AT/1EL = ICAT Shallow New Construction / 120V Electronic / 50W
- NL-402S = Non-IC Shallow New Construction / 120V Magnetic / 50W
- NL-402S/1EL = Non-IC Shallow New Construction / 120V Electronic / 50W
- NLR-403S = Non-IC Shallow Remodel / 120V Magnetic / 50W
- NLR-403S/1EL = Non-IC Shallow Remodel / 120V Electronic / 50W
- NLR-404QAT/20 = Non-IC AT Remodel / 120V Magnetic / 20W
- NLR-404QAT = Non-IC AT Remodel / 120V Magnetic / 50W
- NLR-404AT/1EL = Non-IC AT Remodel / 120V Electronic / 50W
- NLR-404AT/2EL = Non-IC AT Remodel / 277V Electronic / 50W
- NLR-404/75/2EL = Non-IC Remodel / 277V Electronic / 75W

Line Voltage

- NSEIC-407AT/20 = ICAT LED New Construction / 20W
- NSERIC-407AT/20 = ICAT LED Remodel / 20W
- NFBIC-401AT/25A = Fire Rated IC Air-Tight New Construction / 25W
- NSLIC-401AT/10 = ICAT New Construction / 50W
- NSL-401AT/10 = Non-IC Air-Tight New Construction / 50W
- NSLR-404AT/10 = Non-IC Air-Tight Remodel / 50W

Product Images



NL-465B
Black Trim



NL-465BZ
Bronze Trim



NL-465C
Chrome Trim



NL-465S
Silver Trim



NL-465W
White Trim

4" Round Surface Adjustable

Catalog No.

- NL-465B = Round Surface Adjustable, Black finish
- NL-465BZ = Round Surface Adjustable, Bronze finish
- NL-465C = Round Surface Adjustable, Chrome finish
- NL-465W = Round Surface Adjustable, White finish

Optional Accessory

Description

- NT-350 = Black Snoot

Example: NL-465W = 4" Round Surface Adjustable, White finish