

NL-469

4" 45° Adjustable Reflector with Metal Ring

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.050 aluminum bias cut high grade reflector for full lamp distribution. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 45°.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

COMPATIBLE LAMP / HOUSINGS

Low Voltage:

50W MR16 max.

(NLIC-401AT/1EL; NLIC-401AT/2EL; NLIC-401QAT; NL-401AT/1EL; NL-401QAT; NLR-404AT/1EL; NLR-404AT/2EL; NLR-404QAT 75W MR16 max. (NLR-404/75/2EL)

Line Voltage:

20W MR16 GU10 max. (NSEIC-407AT/20; NSERIC-407AT/20)

25W MR16 GU10 max. (NFBIC-401AT/25A)

50W MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

IMPORTANT: DO NOT USE GLASS LENS WHEN ALREADY USING LAMP W/ GLASS COVER

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



PRODUCT IMAGES AND DIMENSIONS




NL-469BZ

Bronze Reflector
Bronze Metal Ring



NL-469W

Specular White Reflector
White Metal Ring



4" 45° Adjustable Reflector with Metal Ring

Catalog No.

NL-469BZ = Bronze Reflector with Bronze Metal Trim

NL-469W = Specular White Reflector with White Metal Trim

Compatible Housings

Catalog No.

Low Voltage

NLIC-401QAT = ICAT New Construction / 120V Magnetic / 50W

NLIC-401AT/1EL = ICAT New Construction / 120V Electronic / 50W

NLIC-401AT/2EL = ICAT New Construction / 120V Electronic / 50W

NL-401QAT = Non-IC AT New Construction / 120V Magnetic / 50W

NL-401AT/1EL = Non-IC AT New Construction / 120V Electronic / 50W

NLR-404QAT = Non-IC AT Remodel / 120V Magnetic / 50W

NLR-404AT/1EL = Non-IC AT Remodel / 120V Electronic / 50W

NLR-404AT/2EL = Non-IC AT Remodel / 277V Electronic / 50W

NLR-404/75/2EL = Non-IC Remodel / 277V Electronic / 75W

Line Voltage

NSEIC-407AT/20 = ICAT LED New Construction / 20W

NSERIC-407AT/20 = ICAT LED Remodel / 20W

NFBIC-401AT/25A = Fire Rated IC Air-Tight New Construction / 25W

NSLIC-401AT/10 = ICAT New Construction / 50W

NSL-401AT/10 = Non-IC Air-Tight New Construction / 50W

NSLR-404AT/10 = Non-IC Air-Tight Remodel / 50W

Example: **NL-469W** = 4" Adjustable Specular White Reflector with White Metal Trim