

NL-4855

4" Square Trim with 2" Square Pinhole

Type

Project

Catalog No.

Notes

FEATURES

Trim: Die-cast aluminum square flange provides sharp clean corners. Non-reflective painted finishes. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

COMPATIBLE LAMP / HOUSINGS

Low Voltage:

20W MR16 max. (NL-401QAT/20; NLIC-401QSAT/20; NLR-404QAT/20; NLIC-402SAT/20; NL-402S/20; NLR-403S/20)
37W MR16 max. (NL-401QAT/37; NLIC-401QSAT/37; NLR-404QAT/37; NLIC-402QSAT/37; NL-402S/37; NLR-403S/37)
50W MR16 max. (NLIC-401AT/1EL; NLIC-401QSAT; NL-401AT/1EL; NL-401QAT; NLR-404AT/1EL; NLR-404QAT; NLIC-402AT/1EL; NLIC-402QSAT; NL-402S/1EL; NL-402S; NLR-403S/1EL; NLR-403S)

Line Voltage:


20W MR16 max. (NSEIC-407AT/20; NSERIC-407AT/20)
25W MR16 max. (NFBIC-401AT/25A)
50W MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



Product Dimensions



Compatible Housings

Catalog No.


Low Voltage

- NLIC-401QSAT/20 = ICAT New Construction / 120V Magnetic / 20W
- NLIC-401QSAT/37 = ICAT New Construction / 120V Magnetic / 37W
- NLIC-401QSAT = ICAT New Construction / 120V Magnetic / 50W
- NLIC-401AT/1EL = ICAT New Construction / 120V Electronic / 50W
- NL-401QAT/20 = Non-IC AT New Construction / 120V Magnetic / 20W
- NL-401QAT/37 = Non-IC AT New Construction / 120V Magnetic / 37W
- NL-401QAT = Non-IC AT New Construction / 120V Magnetic / 50W
- NL-401AT/1EL = Non-IC AT New Construction / 120V Electronic / 50W
- NLIC-402QSAT/20 = ICAT Shallow New Construction / 120V Magnetic / 20W
- NLIC-402QSAT/37 = ICAT Shallow New Construction / 120V Magnetic / 37W
- NLIC-402QSAT = ICAT Shallow New Construction / 120V Magnetic / 50W
- NLIC-402AT/1EL = ICAT Shallow New Construction / 120V Electronic / 50W
- NL-402S/20 = Non-IC Shallow New Construction / 120V Magnetic / 20W
- NL-402S/37 = Non-IC Shallow New Construction / 120V Magnetic / 37W
- NL-402S = Non-IC Shallow New Construction / 120V Magnetic / 50W
- NL-402S/1EL = Non-IC Shallow New Construction / 120V Electronic / 50W
- NLR-403S/20 = Non-IC Shallow Remodel / 120V Magnetic / 20W
- NLR-403S/37 = Non-IC Shallow Remodel / 120V Magnetic / 37W
- NLR-403S = Non-IC Shallow Remodel / 120V Magnetic / 50W
- NLR-403S/1EL = Non-IC Shallow Remodel / 120V Electronic / 50W
- NLR-404QAT/20 = Non-IC AT Remodel / 120V Magnetic / 20W
- NLR-404QAT/37 = Non-IC AT Remodel / 120V Magnetic / 37W
- NLR-404QAT = Non-IC AT Remodel / 120V Magnetic / 50W
- NLR-404AT/1EL = Non-IC AT Remodel / 120V Electronic / 50W


Line Voltage

- NSEIC-407AT/20 = ICAT LED New Construction / 20W
- NSERIC-407AT/20 = ICAT LED Remodel / 20W
- NFBIC-401AT/25A = Fire Rated IC Air-Tight New Construction / 25W
- NSLIC-401AT/10 = ICAT New Construction / 50W
- NSL-401AT/10 = Non-IC Air-Tight New Construction / 50W
- NSLR-404AT/10 = Non-IC Air-Tight Remodel / 50W

Product Images



NL-4855BW
Black Pinhole
White Trim



NL-4855WW
White Pinhole
White Trim

4" Square Trim with 2" Square Pinhole

Catalog No.

- NL-4855BW = Black Pinhole with White Trim
- NL-4855WW = White Pinhole with White Trim

Example: NL-4855BW = 4" Square White Trim with Black Pinhole