

# NL-670

## 6" Baffle with Adjustable Spot Cylinder and Ring

Type

Project

Catalog No.

Notes

### FEATURES

**Trim:** Precision spun metal baffle with deep grooves to reduce aperture glare. Non-reflective painted finishes. Adjustable metal trim can be rotated 358° horizontally and 35° vertically. Separate trim ring available in plastic or metal, may also be used with custom combination of ring finishes.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE LAMP / HOUSINGS

#### Line Voltage:

45W PAR16 Max. (NH-260; NH-270; NHIC-17/100DWQA; NHIC-17QAT; NHIC-17QNBAT; NHIC-27QAT; NHR-260; NHR-270; NHRIC-17QAT; NHRIC-17QNBAT; NHRIC-27QAT)

#### Low Voltage:

20W-50W 12V MR16 (NLIC-601 Series; NL-601 Series; NLR-604 Series)  
20W-75W 12V MR16 (NL-601/75 Series; NLR-604/75 Series)

#### Retrofit Kits:

50W 120V MR16 GU10 Max. (NRA-34/10)  
20W-50W 12V MR16 (NLK-2600)


See individual housing specification sheets for more information.

### LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing



### PRODUCT IMAGES & DIMENSIONS



### Compatible Housings

Catalog No.

#### Line Voltage

- NH-260 = Non-IC New Construction / 45W max
- NHR-260 = Non-IC Remodel / 45W max
- NHIC-17QAT = IC Air-Tight New Construction / 45W max
- NHIC-17QNBAT = IC Air-Tight New Construction / 45W max
- NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 45W max
- NHRIC-17QAT = IC Air-Tight Remodel / 45W max
- NHRIC-17QNBAT = IC Air-Tight Remodel - No Bracket / 45W max
- NH-270 = Non-IC Shallow New Construction / 45W max
- NHR-270 = Non-IC Shallow Remodel / 45W max
- NHIC-27QAT = IC Air-Tight New Construction / 45W max
- NHRIC-27QAT = IC Air-Tight Remodel / 45W max

#### Low Voltage

- NL-601Q = Non-IC New Construction / 120V Magnetic / 20W-50W max
- NL-601/1EL = Non-IC New Construction / 120V Electronic / 3W-50W max
- NL-601/2EL = Non-IC New Construction / 277V Electronic / 20W-50W max
- NL-601/75Q = Non-IC New Construction / 120V Magnetic / 20W-75W max
- NL-601/75/1EL = Non-IC New Construction / 120V Electronic / 20W-75W max
- NL-601/75/2EL = Non-IC New Construction / 277V Electronic / 20W-75W max
- NLIC-601QAT = ICAT New Construction / 120V Magnetic / 20W-50W max
- NLIC-601/1EL = ICAT New Construction / 120V Electronic / 3W-50W max
- NLIC-601/2EL = ICAT New Construction / 277V Electronic / 20W-50W max
- NLR-604/1EL = Non-IC Remodel / 120V Electronic / 3W-50W max
- NLR-604/2EL = Non-IC Remodel / 277V Electronic / 20W-50W max
- NLR-604/75Q = Non-IC Remodel / 120V Magnetic / 20W-75W max
- NLR-604/75/1EL = Non-IC Remodel / 120V Electronic / 20W-75W max
- NLR-604/75/2EL = Non-IC Remodel / 277V Electronic / 20W-75W max

#### Low Voltage Retrofit Kits

NLK-2600 = Non-IC / 120V Magnetic

#### Line Voltage Retrofit Kit

NRA-34/10 = Non-IC / Without Lamp

## 6" Baffle with Adjustable Spot Cylinder and Ring

Catalog No.

NL-670W = 6" White Baffle and Adjustable Spot Cylinder with White Plastic Ring

Example: NL-670W = 6" White Baffle and Adjustable Spot Cylinder with White Plastic Ring