

# NOX-5631

## 5"/6" Onyx Retrofit Reflector

Source: 12.5W or 17.5W LED  
750lm or 1200lm

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

Onyx 5"/6" Round Series is suitable for use with most 5" and 6" recessed housings. Die-cast aluminum construction provides clean sharp edges. Deep regressed optics and round aperture delivers even and glare-free illumination

### FEATURES

- 1200lm / 17.5W or 750lm / 12.5W
- Integral dimmable driver
- Includes medium base socket adaptor for easy retrofitting in 5" or 6" recessed housings
- 5-year limited warranty
- cULus classified for wet locations

### SPECIFICATION

**Trim:** One piece, die-cast aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

**Housings:** Compatible with most 5" and 6" IC and non-IC housings by Nora and others.

**Mounting:** Two steel, spring mounting springs allow for easy and secure mounting in most 5" and 6" housings.

**Optics:** Nora specified and designed precision-molded lens for optimal lumen output and even distribution. The white polymer lens diffuser evenly distributes the light.

**Retrofit:** Luminaires include a medium base screw-socket adapter (NRA-21ISM) for retrofitting into medium base downlight housings. Intended to be used as a LED lamp replacement. GU24 socket adapter (NRA-212SM) is available.

### ELECTRICAL

**Input Voltage:** 120V 60Hz

**Lumens / Wattage:**

(blank) = 750lm / 12.5W; /12 = 1200lm / 17.5W;

Color Temperature: 3500K or 5000K

Color Rendering Index: 90+CRI

Dimming: Down to 5% with ELV or 10% with Triac

[Click Here](#) or check complete dimmer list at

www.NoraLighting.com in the "Compatibility" page under "Resources" tab

### COMPATIBLE HOUSINGS

Onyx retrofits are compatible with most 5" & 6" IC and Non-IC housings by Nora and others.

#### Fire Box

[NFBC-5INCATA](#)

5" ICAT Fire Box

[NFBC-5LMRATA\\*](#)

5" ICAT Dedicated LED Fire Box

[NFBC-6INCATA](#)

6" ICAT Fire Box

[NFBC-6LMRATA\\*](#)

6" ICAT Dedicated LED Fire Box

#### New Construction

[NHIC-5LMRAT\\*](#)

5" ICAT Dedicated LED

[NHIC-5LMRAT/277\\*1](#)

5" ICAT Dedicated LED, 277V

[NHIC-527LMRAT\\*](#)

5" ICAT Shallow Dedicated LED

[NHIC-501QAT](#)

5" ICAT Line Voltage

[NHIC-527QAT](#)

5" ICAT Shallow Line Voltage

[NHIC-6LMRAT\\*](#)

6" ICAT Dedicated LED

[NHIC-6LMRAT/277\\*1](#)

6" ICAT Dedicated LED, 277V

[NHICCP-6LMRAT\\*](#)

6" Chicago Plenum Dedicated LED

[NHIC-27LMRAT\\*](#)

6" ICAT Shallow Dedicated LED

[NHIC-17QAT](#)

6" ICAT Line Voltage

[NHIC-17QNBAT](#)

6" ICAT Line Voltage (No Bracket)

[NHIC-27QAT](#)

6" ICAT Shallow Line Voltage

[NH-26Q](#)

6" Line Voltage

[NHIC-6G24ATFL](#)

6" ICAT GU24

#### Remodel

[NHRIC-5LMRAT\\*](#)

5" ICAT Dedicated LED

[NHRIC-527LMRAT\\*](#)

5" ICAT Shallow Dedicated LED

[NHRIC-504QAT](#)

5" ICAT Line Voltage

[NHRIC-527QAT](#)

5" ICAT Shallow Line Voltage

[NHRIC-6LMRAT\\*](#)

6" ICAT Dedicated LED

[NHRIC-27LMRAT\\*](#)

6" ICAT Shallow Dedicated LED

[NHRIC-17QAT](#)

6" ICAT Line Voltage

[NHRIC-17QNBAT](#)

6" ICAT Line Voltage (No Bracket)

[NHRIC-27QAT](#)

6" ICAT Shallow Line Voltage

[NHR-26Q](#)

6" Line Voltage

\* Nora LED Dedicated housings are cULus listed for use only with Nora LED Retrofits.

<sup>1</sup> Housings are not compatible with 1200lm luminaires

<sup>2</sup> Housings include a step down transformer

### LABELS AND LISTINGS

- cULus classified for Wet Locations
- [5-Year Limited Warranty](#)
- Meets ASTM-E283 Air-Tight requirements
- Certified to the high efficacy requirements of California Title 24 JA8-2022



### PRODUCT IMAGES AND DIMENSIONS





**NOX-5631WW**  
White Reflector, White Flange



**NOX-5631WW / NOX-56EYELIDW**  
White Eyelid



**NOX-5631WW / NOX-56OR-W**  
White Oversize Ring



## 5"/6" Onyx Retrofit Reflectors

Lumens / Wattage / Color Temperature / Finish

**NOX-56315WW/12** = 1200lm / 17.5W / 3500K / White

**NOX-56315OWW** = 750lm / 12.5W / 5000K / White

**NOX-56315OWW/12** = 1200lm / 17.5W / 5000K / White

## Optional Accessories

Description

**NOX-56EYELIDW** = 5"/6" Round Eyelid, White

**NOX-56OR-W** = 5"/6" Round Oversize Ring, White

**NRA-21ISM** = Medium base screw-in socket (included w/luminaire)

**NRA-212SM** = Socket adapter for use with GU24 housing

Example: **NOX-56315OWW/12** = 5"/6" Onyx Round Reflector LED Retrofit, 5000K, White finish, 1200lm / 17.5W