

NAPK-5030HW/12 / NATL-5060HW/12

12V Class II Non-Dimmable Hardwire LED Driver

Source: 100-240V Input / 12V Output
30W or 60W

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

12V enclosed driver to be used with Nora Lighting's 12 Volt systems.

FEATURES

- Type 3R rainproof enclosure
- Non-dimmable
- Conduit access wiring compartment
- Meet Class II output limits
- 12V DC rated output
- Includes 10' power line connector (NALTL-10)
- cULus listed enclosure & cULus recognized driver

ELECTRICAL

Input Voltage: 100-240V

Output Voltage: 12VDC

Wattage: 30W (NAPK-5030HW/12) or 60W (NAPK-5060HW/12)

Dimming: Non-Dimmable

COMPATIBLE NORA 12V SYSTEMS

LED Drivers are compatible with Nora Lighting's 12V systems

SERIES	DESCRIPTION
NUTP4	12V Standard Tape Light
NUTP6	12V RGB Color Changing Tape Light
NMP-LED	12V Josh Puck Light
NM1-170	12V 1" M1 Series

OPTIONAL ACCESSORIES

NALTL-10: 10' Power Line Connector (included)

NALTL-30: 30' Power Line Connector


NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

LABELS AND LISTINGS

- cULus Listed
- FCC compliant



PRODUCT IMAGES & DIMENSIONS



NAPK-5030HW/12 / NAPK-5060HW/12

12V Class II Non-Dimmable Hardwire LED Driver



NALTL-10 / NALTL-30

Power Line Connector (10' included)



NATL-302W

Power Line Splitter

12V Class II Non-Dimmable Hardwire LED Driver

Output Voltage / Wattage

NAPK-5030HW/12 = 12V Output / 30W

NAPK-5060HW/12 = 12V Output / 60W

Optional Accessories

Description

NALTL-10 = 10' Power Line Connector (included w/each driver)

NALTL-30 = 30' Power Line Connector

NATL-302W = Power Line Splitter, White

Example: **NAPK-5060HW/12** = 12V 60W Class II Non-Dimmable Hardwire LED Driver