NATL-5060-12-HWD10

12V Class II Dimmable Hardwire LED Driver (0-10V dimming)

Source: 120-277V Input / 12V Output

60W

PRODUCT DESCRIPTION

12V enclosed dimmable driver to be used with Nora Lighting's 12 Volt systems.

FEATURES

- · 0-10V dimming
- · Conduit access wiring compartment
- · Meet Class II output limits
- · 12V DC rated output
- · Includes 10' power line connector (NALTL-10)
- · cULus listed enclosure & cULus recognized driver

ELECTRICAL

Input Voltage: 120-277V Output Voltage: 12VDC Wattage: 60W THD: <20% Power Factor: 0.95 Dimming: 0-10V

Protection: Short circuit, over voltage and over-temperature protection

COMPATIBLE NORA 12V SYSTEMS

LED Drivers are compatible with Nora Lighting's 12V systems

SERIES DESCRIPTION
NMP 12V Josh Puck Light
NM1-170 12V 1" M1 Series

OPTIONAL ACCESSORIES

NALTL-10: 10' Power Line Connector (included)

NALTL-30: 30' Power Line Connector

NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.


LABELS AND LISTINGS

- · cULus Listed Enclosure
- · cULus Recognized Driver



Type Project Catalog No. Notes

PRODUCT IMAGES & DIMENSIONS



NATL-5060-12-HWD10
12V Class II Dimmable Hardwire LED Driver
0-10V dimming



NALTL-10 / NALTL-30 Power Line Connector (10' included)



NATL-302W Power Line Splitter

12V Class II Dimmable Hardwire LED Driver (0-10V dimming)	Optional Accessories
Output Voltage / Wattage	Description
NATL-5060-24-HWD10 = 12V Ouput / 60W	NALTL-10 = 10' Power Line Connector (included w/each driver) NALTL-30 = 30' Power Line Connector NATL-302W = Power Line Splitter, White

Example: NATL-5060-12-HWD10 = 12V 60W Class II Dimmable Hardwire LED Driver (0-10V dimming)

