

NE-806

Beveled Integral Dual Head Emergency Light

Lamp: (2) 5VA/T5WB

PRODUCT DESCRIPTION

Dual-head DC emergency light with 120V/277V AC Charging. Low profile integrated design. Provides 90 minute illumination during power loss. Internal solid-state circuitry automatically switches fixture between charging/standby and emergency operation.

CONSTRUCTION

- 11-13/16" Width X 5" Height X 2-11/16" Depth
- Injection-molded housing with access for ceiling or wall power supply

FACE

- Injection molded face with two clear polycarbonate covers on beveled surfaces.

MOUNTING

- Wall or Ceiling
- Mounting hardware included

ELECTRICAL

Voltage: Dual 120V/277V input
 Automatic solid state switching and charging
 Automatic reset
 Quick wire connection - no extra hardware necessary
 Light Source

Battery: Replaceable 6V, 4A lead-calcium maintenance-free battery for backup operation during power loss
 90 minute emergency operation on fully charged battery

TESTING

- High-charge/Ready operation indicator light
- Test button

CIRCUITRY PROTECTION

- Isolated surge/short circuit protection

OPERATING LIFE EXPECTANCY



4 Years

LABELS AND LISTINGS

- UL 924 Compliant
- ETL Listed
- NEC
- NFPA
- State & Municipal
- Suitable for damp Location



PRODUCT IMAGES & DIMENSIONS



2-11/16"



11-13/16"



5"

Beveled Integral Dual Head Emergency Light

Catalog No.

NE-806 (2) 6W T5 wedge base Emergency Light w/Battery Backup, White Finish

Example: **NE-806** = Beveled Integral Dual Head Emergency Light, White