

## NE-871LEDW & NE-872LEDW

Single Head, 1W LED Lamp, White

### PRODUCT DESCRIPTION

Remote head fixtures provides a superior aiming and flexible appearance along with excellent performance. Dual lighting heads provide strong ambient light levels to assist in emergency egress during power failure. Internal solid state switching automatically activates fixture during power loss.

### FEATURES

- Fully adjustable glare-free square shape light heads with positive positioning lock
- Reilable slide friction position hold
- Injection molded thermoplastic housing
- Suitable for Damp location

**Housing:** Injection-molded thermoplastic ABS housing. Plastic enclosure with 5VA flame retardant. (NE-872LED) Two fully adjustable glare-free square shape light heads for emergency light.

### ELECTRICAL

**Voltage:** 3.6VDC, power from low voltage power source (not provided)

**Power Consumption:** 1W(NE-871LED)  
2W(NE-872LED)

**Light Source:** 1W (6 LEDs) per head (NE-871LED)  
Two 1W (6 LEDs) head (NE-872LED)

**Lumens:** 75lm at 3ft (NE-871LEDW)  
150lm at 3ft (NE-872LEDW)

**Operating Temp:** 0°C to 40°C ambient temperature

**Life Expectancy:** 35,000 Hours

**Mounting:** Suitable for wall mounting, ceiling mounting and side mounting.  
Housing snaps to canopy with a simple twist and lock.


### LABELS AND LISTINGS

- Suitable for Damp Location
- UL, cUL Listed and meets or exceeds all requirements in NFPA 70, NFPA 101 life safety code




### PRODUCT IMAGES AND DIMENSIONS

#### NE-871LEDW Single Head, 1W LED Lamp



#### NE-872LEDW Double Head, 1W x 2 LED Lamp



### Slim Type LED Emergency Light

Catalog No.

**NE-871LEDW** Single Head, 1W LED Lamp, White

**NE-872LEDW** Double Head, 1W x 2LED Lamp, White

Example: **NE-871LEDW** = Single head, 1W LED Lamp, White