

NLOP-R6509

6" Opal - LED Surface Mount

Source: 13W LED
1050lm

PRODUCT DESCRIPTION

The Opal LED Series LED fixture is designed to surface mount over a standard junction box. The low profile dimmable luminaire produces even illumination and is cULus listed for wet locations.

FEATURES

- Dimmable
- 2700K @ 90+ CRI
- Mount on standard 4" junction box
- ENERGY STAR certified

SPECIFICATION

Construction: One piece aluminum die formed housing and trim. Aluminum body dissipates heat and extends life.

Mounting: Suitable for installation on most 4" square, octagon or round electrical junction boxes with a minimum depth of 2-1/8". Can be used with 4" fire rated electrical junction boxes. Luminaires can also be mounted on 5" or 6" recessed housings using optional torsion spring kit (NLOPAC-56RECKIT-2).

Optics: Nora specified and designed precision molded lens for optimal lumen output and even distribution.

Ratings: IC rated when used with a 4" electrical junction box rated for direct contact with insulation. Fire rated when used with a fire rated junction box.

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage: 1050lm / 13W

Color Temperature: 2700K

Color Rendering Index: 90+ CRI

Dimming: 5% with Triac or 10% with ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

ACCESSORIES

NLOPAC-56RECKIT-2: Opal can be mounted in 5" or 6" recessed housings using optional torsion spring kit.

LISTING

- cULus Listed for wet locations (covered ceiling only)
- ENERGY STAR certified
- [5-Year Limited Warranty](#)




Type _____

Project _____

Catalog No. _____

Notes _____

PRODUCT IMAGES AND DIMENSIONS



NLOPAC-56RECKIT-2

Retrofit Kit for 5" or 6" Recessed Housings

6" Opal - LED Surface Mount

Color Temperature / Finish

NLOP-R650927AW = 2700K / White

Optional Accessories

Description

NLOPAC-56RECKIT-2 = Retrofit Kit for 5" or 6" Recessed Housings

Example: **NLOP-R650927AW** = 6" Opal, 1050lm / 13W, 2700K, White finish