

NMPK Series

12V LED Puck Light

Source: 2.4W LED
210lm

Type _____

Project _____

Catalog No. _____

Notes _____

PRODUCT DESCRIPTION

Nora Lighting introduces a new slim light disk LED system for accent, under cabinet, cove lighting and jewelry cases, and other applications with limited space. These low-profile fixtures can be chained together to provide excellent and even illumination on all surfaces. Light disk is one of the most energy efficient products in the market. Combined with ultra low-profile housing, Nora's light disk offers unique features and a great ease of installation. LED technology eliminates forward heat from the fixture, also no UV or infrared rays to harm artwork, retail displays or heat sensitive foods.

FEATURES

- LEDs produce 210 lumens (70 lumens per watt)
- Ten lights can be daisy-chained up to 90' away from driver
- Bronze, Chrome or White finish
- Well suited for very small spaces: 1/2" deep with 2-3/4" diameter
- Easy installation using one screw
- 3", 6", 12" and 24" interconnection cables included with each puck
- Dimmable with Magnetic Power Supply
- cETLus listed for dry locations
- 30,000 hours of rated lamp life

Included with each LED Puck: (1) Mounting Clip and Screw, (1) 3" Interconnection Cable [NAPK-702], (1) 6" Interconnection Cable [NAPK-706], (1) 12" Interconnection Cable [NAPK-712], (1) 24" Interconnection Cable [NAPK-724] and (1) Mini Coupler [NAPK-713]

ELECTRICAL

Input: 12VDC

Lumens / Wattage: 210lm / 4.2W

Color Temperature: 4200K

Max Run Length: 10.7' (w/ NMT-60/12C2) or 14.2" (w/ NAPK-560HW/12)


Dimming: Dimmable with Magnetic Power Supply

LABELS AND LISTINGS

- cULus Listed for Dry Location
- 3-Year Limited Warranty
- RoHS compliant



PRODUCT IMAGES AND DIMENSIONS



NMPK LED Puck Light

Description	12V LED Drivers	Driver Accessories	Accessories			
			Connectors	Power Feed	Others	Finish
NMPK1-3LED42BZ = 4200K / Bronze Finish	NMTD-40/12D	NALTL-10	NAPK-702 NAPK-703 NAPK-706 NAPK-712 NAPK-724 NAPK-736 NAPK-748	NAPK-709 NAPK-711	NAPK-701 NAPK-713 NMPKA-RECW NMPKA-RECBZ NMPKA-RECC NATL-415	B = Black W = White
NMPK1-3LED42C = 4200K / Chrome Finish	NMTD-60/12D	NALTL-30				
NMPK1-3LED42W = 4200K / White Finish	NAPKED-5040HW	NATL-302W				
	NAPKED-5060HW					
	NMT-244/12C2D1					
	NMT-244/12C2D2					
	NATL-5060-12-HWD10					

Example: NMPK1-3LED42W / NMTD-60/12D / NALTL-30 / NAPK-702W

NMPK Series

12V LED Puck Light
Accessories

Type
Project
Catalog No.
Notes



Splitter

NMPK-701B Black
NMPK-701W White
To separate 4 puck light runs from a single driver or to split a run between puck lights. One in and four out.



Interconnection Cable

NAPK-702 2" Cable
NAPK-703 3" Cable
NAPK-706 6" Cable
NAPK-712 12" Cable
NAPK-724 24" Cable
NAPK-736 36" Cable
NAPK-748 48" Cable
Finish: Black (B), White (W)
Allows easy linking of two pucks.



Mini Coupler

NAPK-713B Black
NAPK-713W White
Used to connect two interconnection cables together or to add interconnection cable to power line interconnector.
Dim.: 3/8" W; 3/4" L; 1/4" H



Power Line Interconnector

NAPK-711B 12" black w/switch
NAPK-711W 12" white w/switch
NAPK-709B 18" black
NAPK-709W 18" white
Connects puck light to a driver.



Recessed Housing Accessory

NMPKA-RECBZ Bronze
NMPKA-RECC Chrome
NMPKA-RECW White
Used to mount puck light recessed and flush



2' Wire Raceway

NATL-422B Black
NATL-422W White
Field-cutable plastic. Includes wire channel with double faced tape and cover.



Power Line Connector

NALTL-10 10' Cable
NALTL-30 30' Cable
For use with Class II drivers. Carries output from driver, requires power line cable. 5" Power Line Splitter
NATL-302W



Low Voltage Splice Box

NATL-415W
Use to join low voltage lead to low voltage power line connector or interconnector.



Direct Plug-In LED Driver

NAPK-524W/12 White 24W
NAPK-560W/12 White 60W
Voltage: 120V/12V
Wattage: 24W or 60W
Dimming: Non-Dimmable
Cable Length: 4' cord & plug and 48" power line connector for NAPK-560W/12



Class II Hardwire LED Driver with Regulator, MLV Dimming
NMTD-40/12D 40W
NMTD-60/12D 60W
Voltage: 120-277V/12V
Wattage: 40W or 60W
Dimming: Magnetic Low Voltage
Regulator: Integral regulator for constant current and voltage
Includes: 10' Power Line Connector



Class II Hardwire LED Driver ELV Dimming
NAPKED-5040HW 12V 40W
NAPKED-5060HW 12V 60W
Input Voltage: 120V
Dimming: Electronic Low Voltage
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming
NMT-244/12C2D1 120/12V 240W
NMT-244/12C2D2 277/12V 240W
Input Voltage: 120V or 277V
Dimming: Magnetic Low Voltage
Wattage: (4) 60W
Includes: (4) 10' Power Line Connectors



Class II Hardwire LED Driver 0-10V Dimming
NATL-5060-12-HWD10 60W
Voltage: 120-277V/12V
Wattage: 60W
Dimming: 0-10V
Includes: 10' Power Line Connector