

# NMRT-1

## Flanged Gimbal Comfort Dim LED Multiple Lighting Trim (Housing Required)

Source: 11W to 37W LED

850lm to 3000lm per head

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

A beautiful enclosed steel face plate. Gimbal regressed 1.5 inch for a clean ceiling appearance. Available in 1, 2 and 3 LED linear configurations. Excellent for flexible general lighting in commercial and architectural applications.

### CONSTRUCTION

**Trim:** The aluminum face plate is a flanged seamless stamped metal. Each LED gimbal adjusts independently at 40° with 350° rotation.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing.

**Trim Style:** Trim is available in two styles; 1-1/2" regressed or flat face. Flat face is only available in white finish.

**Finish:** Flange is available in silver or white finish. Regressed face is available in black, silver or white finish.

### ELECTRICAL

**Input Voltage:** 120V or 277V

**Lumens / Wattage:** **L85** = 850lm / 11W; **L20** = 2000lm / 25W; **L30** = 3000lm / 37W

**CRI:** 90+CRI

**Operating Temp.:** 0°C to 45°C ambient temperature

**Comfort Dim:** Comfort Dim color tunes the temperature from a bright 2700K, to a romantic and comfortable 1800K on a gradual, even curve.

Comfort Dim is available in 4 different lumen levels:

- 850 Lumens for lower ceiling heights in commercial and residential applications.
- 2000 Lumens for light commercial and residential high ceiling applications
- 3000 Lumens for commercial high ceiling applications

**Dimming:** ELV or 0-10V dimming


[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

### COMPATIBLE LED HOUSING

Catalog No. Description

**NMRG-1** Flanged Gimbal Comfort Dim LED Housing

### PRODUCT IMAGES AND DIMENSIONS



Dimensions	Length (A)
1 Head	9-3/4"
2 Head	18"
3 Head	23-3/4"

### LABELS AND LISTINGS

- cULus Listed for damp locations
- ENERGY STAR certified
- 5-Year Limited Warranty



### Flanged Gimbal Comfort Dim LED Multiple Lighting Trim - Housing ordered separately

Face Type	Number of Heads	Lumens / Wattage Per Head	Color Temp.	Face / Flange Finish
<b>NMRT-1</b> = Regressed Face	<b>1</b> = One Head	<b>L85</b> = 850lm / 11W	<b>CD</b> = Comfort Dim	<b>BW</b> = Black / White
<b>NMRT-1F</b> = Flat Face*	<b>2</b> = Two Heads	<b>L20</b> = 2000lm / 25W		<b>SS</b> = Silver / Silver
	<b>3</b> = Three Heads	<b>L30</b> = 3000lm / 37W		<b>WW</b> = White / White

\* Flat face available in White / White finish only

Example: **NMRT-12L20CDBW** = Two Head Regressed Face Flanged Gimbal Comfort Dim LED Multiple Lighting Trim, 2000lm / 25W per head, Black Face / White Flange