

NMT-303/24C2D1 / NMT-303/24C2D2

24V Class II Dimmable Hardwire Magnetic LED Driver with Breakers

Source: 120V or 277V Input / 24V Output
300W (3 x 100W Breakers)

Type	
Project	
Catalog No.	
Notes	

PRODUCT DESCRIPTION

24V enclosed dimmable driver to be used with Nora Lighting's 24 Volt systems requiring a Class II driver. Three breakers each produce 100 watts and can be dimmed with low voltage magnetic dimmer. Includes a regulator to provide constant current and constant voltage.

FEATURES

- Low voltage magnetic dimming
- Integral regulator for constant current and voltage
- Manual Reset Overload Protection for each Class II Circuit
- Indoor/Outdoor Enclosure Type 3R Enclosure
- Conduit Access Wiring Compartment
- Made in USA
- Meets Class II output limits
- 24 Volt DC Rated output
- UL Recognized
- Available in 120V or 277V

ELECTRICAL

Input Voltage: 120V or 277V (must specify)

Output Voltage: 24VDC, 4A per circuit max.

Wattage: 3 x 100W

Dimming: Magnetic Low Voltage

Regulator: Constant Current and Constant Voltage

COMPATIBLE NORA 24V SYSTEMS

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
NUTP1	24V Standard Tape Light (Silicone Encapsulated)
NUTP3	24V RGB Color Changing Tape Light
NUTP5	24V Hy-Brite Tape Light
NUTP7	24V Standard Tape Light (Non-Encapsulated)
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP11	24V RGBW Color Changing Tape Light
NUTP12	24V Comfort Dim Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
NUTP71	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light
NULB	24V Lightbar Silk SBC

OPTIONAL ACCESSORIES

[NALT-10](#): 10' Power Line Connector

[NALT-30](#): 30' Power Line Connector


[NATL-302W](#): Power Line Splitter, white cable. Splits power line connector into two separate connections.

LABELS AND LISTINGS

- [3-Year Limited Warranty](#)
- cULus Recognized Driver



PRODUCT IMAGES & DIMENSIONS



NMT-303/24C2D1 / NMT-303/24C2D2
24V Class II Dimmable Hardwire Magnetic LED Driver



NALT-10 / NALT-30
Power Line Connector



NATL-302W
Power Line Splitter

24V Class II Dimmable Hardwire Magnetic LED Driver with Breakers

Input Voltage / Output Voltage
NMT-303/24C2D1 = 120V input / 24V output
NMT-303/24C2D2 = 277V input / 24V output

Optional Accessories

Description
NALT-10 = 10' Power Line Connector
NALT-30 = 30' Power Line Connector
NATL-302W = Power Line Splitter, White

Example: **NMT-303/24C2D2** = 277V/24V 300W Class II Dimmable Hardwire Magnetic LED Driver with (3) 100W Breakers