NTH-106G24 (GU24 Track)

Roundback Cylinder with Convex Frosted Lens.

Lamp: 26W Twist & Lock Spiral GU24 / 15W Twist &lock R30 G24

PRODUCT DESCRIPTION

Energy efficient GU24 compact fluorescent step cylinder with convex frosted lens. Structural arm provides full adjustment of light source for special aiming and completely conceals wire lead from socket to contact head. Internal mechanism allows for adjustment and resists angle degradiation.

FEATURES

- Deep drawn steel housing for high strength and rigidty
- Completely concealed wiring
- Fully adjustable, firm angle position
- High-strength stainless steel electrical contacts
- One or two circuit track capable

CONSTRUCTION

Housing

0.030 Deep drawn steel construction with simple, yet decorative design. All edges are softened for aesthetic appearance.

Convex Lens

Frosted convex lens provided for even illumination, may be removed for R30 GU24 lamp.

Structural Arm

Extended 0.055 aluminum arm connects fixture housing to electrical contact head. Internal tightening mechanism maintains desired lamp aiming angles. Structural arm also functions as wire way, completely concealing lead wire from socket to contact head.

ELECTRICAL SYSTEM

Socket

Procelain twist & lock GU24 based socket, 600V, 660W.

Lamp

26W Twist & Lock Spiral GU24 lamp maximum (ordered separately) 15W Twist & Lock R30 GU24 lamp maximum (ordered separately)

One/Two Circuit Conversion

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT- 2300 series two-circuit track.

FINISHES

Black, and White powder coated finishes availabe, custom painting or anodizing for special aplications is available. Custom finishes will require lead times that vary depending on vendor schedules. Please consult factory for quotations and provide a Dunn Edwards number or color chip for exact color matcing.

Finishes

 $\mathbf{B} = \text{Black}$ $\mathbf{W} = \text{White}$

LISTING

Catalog No.

NTH-106G24

UL Listed as track lighting fitting.

ENORALIGHTING.

Туре

Project

Catalog No.

Lamp/Wattage

DIMENSIONS



Max. Extension: 9-1/4"





Roundback Cylinder with Convex Frosted Lens