

# NTH-132

Belgium™ Die-Cast PAR30 Front Loading Gimbal

Lamp: 75W PAR30 max.

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

## PRODUCT DESCRIPTION

Line voltage front-loading gimbal fixture. Heavy die-cast construction provides superior strength, rigidity, and heat dissipation. Locking front ring protects lamp and enhances appearance. Front loading capability provides quick, easy lamp maintenance with minimal interference with original fixture aiming.

## FEATURES

- Heavy die-cast construction
- Die-cast Lamp Locking Ring
- Fully adjustable, firm angle position
- High-strength stainless steel electrical contacts
- One or two circuit track capable
- Accepts LED lamps

## CONSTRUCTION

**Housing:** 0.09" Die-cast aluminum two-piece housing with modernistic detail secured together with finished Allen-head screw. Two arms constructed from thick 0.050" die-cast aluminum extend from the housing and contain molds to secure 0.25" die-cast aluminum locking ring.

**Structural Arm:** 0.10" "L" Steel bracket connects fixture housing to electrical contact head. Two finished plastic knobs allow user to lock fixture position to desired angles.

## ELECTRICAL

**Voltage:** 120V input

**Socket:** Medium base

**Lamp:** 75W PAR30 max. (not included)

## ONE/TWO CIRCUIT CONVERSION


Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT- 2300 series two-circuit track.

## LABELS AND LISTINGS

UL Listed



## PRODUCT IMAGES AND DIMENSIONS



## Belgium Die-Cast PAR30 Front Loading Gimbal

Catalog No.	Finishes	Style
NTH-132	B = Black	(blank) = H-style
	S = Silver	/J = J-style
		/L = L-style

Example: NTH-132B = Belgium Die-Cast PAR30 Front Loading Gimbal, Black Finish, H-Style Adapter