

NTH-615
MR16 Newton™ European Die-Case Ring Face
Source: 50W max.
MR16 GU10 (lamp not included)

Type	
Project	
Catalog No.	
Notes	

PRODUCT DESCRIPTION

Low voltage die cast lamp holder with locking steel ring mounted on two posts protruding from face of MR16 light source. Horizontal adjustment friction locked, knob provided to lock vertical adjustment.

FEATURES

- Die-cast aluminum body provides superior strength and rigidity
- Ideal for commercial use.
- Locking ring allows use of light control/effect media accessories.
- One or two circuit track capable.

SPECIFICATION

Construction: Main body consists of a two-piece .080 die cast aluminum housing connected with four polished stainless steel screws. Two additional stainless steel screws secure a porcelain MR16 GU5.3 base socket.

Stem: .08 Rigid steel curved yoke connects fixture housing to integral transformer. Black plastic tightening knob maintains clean, decorative appearance of the fixture and provides secure angle position

Face: Two .2 stainless steel standoffs secure two or more .04 finished oval steel rings to housing in front of MR16 light source. Standoffs secure to front of housing with two hand-tightened chrome finished stainless steel screws.

ELECTRICAL

Socket: Porcelain twist and lock GU10 socket

Wattage: 50W maximum

Lamp: MR16 (not included)

One/Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to “down” position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LISTING


cULus Listed for Dry Locations



PRODUCT IMAGE



PRODUCT DIMENSIONS



Newton™ European Die-Cast Ring Face Track Head

Series	Finish	Adapter Style
NTH-615	S = Silver	(blank) = H-Style /J = J-Style /L = L-Style

Example: **NTH-615S** = Newton™ European Die-Cast Ring Face Track Head, Silver finish, H-Style Adapter