

Pull-Down Adjustable LED Multiple

LED Dedicated Flange and Trimless Style
Single Opening · 1 to 3 Adjustable Lights

Nspec introduces the Pull-Down adjustable LED to the MLS family of multiple lighting products. The Pull-Down units offer the ultimate in flexibility. Each LED module can be left in the housing and be adjusted or can be pulled down partially or completely to gain full adjustability in aiming the fixture. Each module produces 2000 lumens at 90+CRI in 3000K, 3500K, or 4000K CCTs options. Available in white or black finishes, the MLS LED Pull-Down can be specified with spot or flood beam spreads.

FEATURES

- **LED Dedicated**
- 2000 Lumens at 30W per module
- 90+ CRI
- 2700K, 3000K, 3500K and 4000K CCT option
- Specifiable with either Spot or Narrow Flood beam spread
- Dimmable - 120V Triac or 0-10V / 277V 0-10
- Lamps independently adjustable
- Three configurations: one-light square, two- and three-light linear
- Available in white or black finish
- Lower installation and maintenance costs
- Includes mud-in rings
- Can be installed as a remodel or new construction
- Optional new construction frame-in available
- Optional Flange Kit
- 5-year limited warranty



Shown with optional Flange Kit



Pull-Down Adjustable LED Trimless Multiples Lighting System

Series	# of Pulldowns	Driver	Voltage	Lumen Output	Beam Spread	Color Temp	Finish
NMRTLGPD-1	1 = 1 Lamp	D = Standard	1 = 120V	L20 = 2000Lm	S = 15°	27 = 2700	B = Black W = White
	2 = 2 Lamps		2 = 277V		F = 40°	30 = 3000	
	3 = 3 Lamps					35 = 3500	

Example: NMRTLGPD-11D1L20S27W Pull-Down Adjustable LED MLS, single lamp, 2000 lumen, 15° beam spread, 2700K, White finish