# NORA

# **ILENE SERIES** LED Mini Cylinder

The iLENE Cylinder Pendants or Surface mount feature three sizes and outputs. Using Cree COB technology, the iLENE produces 90+ CRI of clean crisp light. The optics are deep set for excellent visual comfort. Each iLENE includes three field changeable optics for spot, narrow flood and flood beam spreads. The canopy mounted driver allows for cool operation and optional driver and dimming options. Specify 2700K, 3000K or 4000K kelvin temperature to meet your application needs. The die-cast aluminum cylinders are available in Black, Silver and White finishes.

## FEATURES

- · Architectural die-cast aluminum construction and style
- Pendant and Surface Mount
- · Cree<sup>®</sup> LED COB or Comfort Dim Technology
- · Deep set optics
- · 2700K, 3000K or 4000K @90+ CRI
- Dimmable (Triac, ELV or 0-10V)
- 120V and 277V
- · Black, Silver and White Finishes (Reflectors match finish)
- Three Sizes and outputs
- · 2" 1000lm / 23W
- 3" 1500lm / 25W
- 5" 2000lm / 35W
- Spot, Narrow Flood and Flood field changeable optics
- 8' Field adjustable cable
- cULus Listed for Damp Location
- ENERGY STAR<sup>®</sup> certified
- · 5-Year Limited Warranty



#### **ILENE** LED MINI CYLINDER

SIZE	MOUNTING OPTION	ССТ	FINISH	DIMMING
NYLM-2 2" NYLM-3 3" NYLM-5 5"	C Cable Pendant SC Surface	27X 2700K 30X 3000K 40X 4000K CD Comfort Dim (3100K to 200K)	BB Black SS Silver WW White	LE3 (Only for NYLM-2) LE4

LE3 = 120V input; Triac/ELV dimming

LE4 = 120V input; Triac/ELV or 0-10V dimming / 277V input; 0-10V dimming

Example: NYLM-5C30XBBLE4 - 5" iLENE LED Mini Cylinder Pendant Mounted, 3000K, Black finish, 120V/277V input; Triac, ELV or 0-10V dimming

### 2" & 3" ILENE OPTIONAL ACCESSORIES

 NIO-AS14AM
 Amber Translucent Decorative Collar

 NIO-AS14BLU
 Blue Translucent Decorative Collar

 NIO-AS14FR
 Frosted Translucent Decorative Collar

 NIO-AS14FR
 Red Translucent Decorative Collar

 NIO-ASI4BLK
 Black Opaque Snoot

 NIO-ASI4MPW
 Matte Powder White Opaque Snoot

 NIO-ASI4WH
 White Opaque Snoot

Three Sizes - 2", 3" and 5" 1000 to 2000 lumens



NYLM-2C NYLM-2SC L: 5-7/8" Dia: 2-3/8"

NYLM-3C NYLM-3SC L: 6-3/4" Dia: 3-3/4"

NYLM-5C NYLM-5SC L: 7-7/8" Dia: 5-1/2"

