

# NHMC-926LMRAT

6" Sloped IC Air-Tight LED Dedicated New Construction Housing  
(Compatible with Marquise I Sloped Reflectors)

Type	
Project	
Catalog No.	
Notes	

## PRODUCT DESCRIPTION

Dedicated new construction housing for sloped ceiling with a 6/12 pitch ceiling. Air-tight housing additionally reduces energy costs by decreasing the flow of air escaping through the ceiling. Rated for direct contact with insulation and adjacent ceiling structures. The housing is dedicated and labeled for use with Marquise I sloped fixtures.

## FEATURES

- IC rated for direct contact with insulation
- Quick connect provided for electrical connection to the LED reflectors
- ASTM E283 for Air-Tight
- 24-1/2" bar hangers with captive nails and alignment foot

## CONSTRUCTION

**Plaster Frame:** High quality .035 steel die cut one piece frame. Bar hanger brackets on all four sides provide two possible positions for installations. Integral brackets and winguts enable housing to be adjusted for 2/12 - 6/12 ceiling pitch.

**Housing:** 0.035 steel housing. Riveted wrap and dome cap construction. Integral fold-out torsion spring brackets. Knockouts near top of housing provided for coil springs.

**Air Flow Restriction:** Housing has factory installed gaskets to restrict airflow from room into ceiling plenum to <2CFM (cubic feet per minute) in accordance with ASTM-283 Air-Tight requirements.

**Clearance:** "IC" Insulated ceiling housings are direct contact rated. **Not to be used in direct contact with spray foam insulation.**

**Bar Hangers:** Two 13-3/4" to 24-1/2" adjustable bar hangers with captive nails are included on frame. Bar hangers are parallel to junction box, but can be repositioned 90° perpendicular to junction box if desired. "L" Shaped bar hanger foot to align to bottom of construction joist. A T-Bar notch allow for easy installation in a suspended ceiling.

**Junction Box:** Prewired 25 cubic inch 0.064" thick galvanized steel with seven 1/2" trade size knockouts and four Romex pryouts and snap on covers. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Through branch circuit wiring, (4-in, 4-out).

## ELECTRICAL

**Input Voltage:** 120V

**Socket:** Quick connect for LED reflectors

**Operating Temp.:** 122°F (50°C) max. ambient temperature

**Dimming:** Specified by reflector

## COMPATIBILITY

NRMC-6S11 - Marquise I Sloped Reflector


NRMC-6S12 - Marquise I Sloped Baffle

## LABELS AND LISTINGS


- cULus Listed for Damp Location
- Meets or exceeds ASTM-283 Air-Tight requirements



## PRODUCT IMAGES & DIMENSIONS



6-1/2" x 7"  
Ceiling Cut-out



## 6" Sloped IC Air-Tight LED Dedicated New Construction Housing

Catalog No.

NHMC-926LMRAT = 6" Sloped LED Dedicated IC Air-Tight Housing, 120V input

Example: NHMC-926LMRAT = 6" Sloped IC Air-Tight LED Dedicated New Construction Housing, 120V input