

NLOPAC-R4509

4" AC Opal - LED Surface Mount

Source: 10.5W LED

650lm

Type _____

Project _____

Catalog No. _____

Notes _____

PRODUCT DESCRIPTION

The AC Opal LED Series LED fixture is designed to surface mount over a standard junction box. The low profile dimmable luminaire produces even illumination and is cULus listed for wet locations.

FEATURES

- AC LED (No Driver)
- Dimmable
- 2700K, 3000K or 5000K @ 90+ CRI
- White, bronze or natural metal finishes
- Mount on standard 4" junction box

SPECIFICATION

Construction: One piece aluminum die formed housing and trim. Aluminum body dissipates heat and extends life.

Mounting: AC Opal (no driver) is flat on the back and suitable for installation on most 4" octagon boxes or 4/0 plaster ring. Luminaires can be installed in covered ceiling and wall mount. Includes universal bracket for 3" or 4" junction boxes.

Optics: Nora specified and designed precision molded lens for optimal lumen output and even distribution.

Finishes: Available in white, bronze and natural metal finishes.

Ratings: IC rated when used with a 4" electrical junction box rated for direct contact with insulation. Fire rated when used with a fire rated junction box.

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage: 650lm / 10.5W

Color Temperature: 2700K, 3000K, 5000K

Color Rendering Index: 90+ CRI

Operating Temperature: 0-45°C

Dimming: 5% with Triac or 10% with ELV


[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

LISTING

- cULus Listed for wet locations (covered ceiling only)
- [5-Year Limited Warranty](#)
- RoHS Compliant
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (A)(1) and 410.16 (C)(1).



PRODUCT IMAGES AND DIMENSIONS



BZ
Bronze



NM
Natural Metal



W
White

4" AC Opal - LED Surface Mount

Color Temperature / Finish

NLOPAC-R450927ABZ = 2700K / Bronze

NLOPAC-R450930ANM = 3000K / Natural Metal

NLOPAC-R450950AW = 5000K / White

Example: **NLOPAC-R450950AW** = 4" AC Opal, 650lm / 10.5W, 5000K, White finish

PHOTOMETRICS

4" AC Opal - LED Surface Mount

Type _____


Project _____

Catalog No. _____

Notes _____

Test Information

Test Number: NTR11246
 Part Number: NLOPAC-R450930AW
 Beam Spread: 108° Wide Flood
 Lumens: 716lm
 Wattage: 10.46W
 Efficacy: 68lpw
 CCT / CRI: 3000K / 90 CRI
 Spacing Criteria (0°-180): 1.22
 Spacing Criteria (90°-270): 1.24



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	15.4fc	10'-11"
6'	6.9fc	16'-5"
8'	3.9fc	21'-11"
10'	2.5fc	27'-4"
12'	1.7fc	32'-10"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	190	26.5
0-40	307	42.9
0-60	536	74.9
0-90	705	98.4
90-180	11	1.6
0-180	716	100

Candela Table

Vertical Angles	Candela
0	247
5	247
15	236
25	216
35	188
45	155