

NP-22

6" Albalite Lens with Plastic Trim

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: High grade albalite lens attached to plastic trim. Lens can be easily removed by hand without tools from below the ceiling for relamping

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

25W A19 Maximum (NHIC-27QAT; NHRIC-27QAT)

40W A19 Maximum (NHIC-17QAT; NHRIC-17QAT)

60W A19 Max. (NH-26Q; NH-27Q; NHIC-17/100DWQA; NHR-26Q; NHR-27Q)

Sloped Line Voltage


40W A19 Maximum (NHIC-926DWQAT; NHIC-926QAT; NHRIC-926QAT)

LABELS AND LISTINGS

- cULus Listed for Wet Location when used with compatible housing.



PRODUCT IMAGES AND DIMENSIONS



6" Albalite Lens with Plastic Trim

Catalog No.

NP-22 = Albalite Lens with White Plastic Trim

Compatible Housings

Catalog No.

- NH-26Q = Non-IC New Construction / 60W max
- NHR-26Q = Non-IC Remodel / 60W max
- NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 60W max
- NHIC-17QAT = IC Air-Tight New Construction / 40W max
- NHRIC-17QAT = IC Air-Tight Remodel / 40W max
- NH-27Q = Shallow Non-IC New Construction / 60W max
- NHR-27Q = Shallow Non-IC Remodel / 60W max
- NHIC-27QAT = Shallow IC Air-Tight New Construction / 25W max
- NHRIC-27QAT = Shallow IC Air-Tight Remodel / 25W max
- NHIC-926DWQAT = Sloped IC Air-Tight New Construction / 40W max
- NHIC-926QAT = Sloped IC Air-Tight New Construction / 40W max
- NHRIC-926QAT = Sloped IC Air-Tight Remodel / 40W max

Example: NP-22 = 6" Albalite Lens with White Plastic Trim