


NP-23

Fresnel Lens with Plastic Trim

TRIM DIMENSIONS



Trim OD: 8"

FEATURES

Trim

High grade fresnel lens attached to plastic trim. Lens can be easily removed by hand without tools from below the ceiling for relamping.

Mounting

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

Compatible Housings

Compatible with Line Voltage, Compact Fluorescent, and CFL Retrofits. See individual specification sheets for more information.

Lamp

Line Voltage

25W A19 Maximum (NHIC-27QAT; NHRIC-27QAT)

40W A19 Maximum (NHIC-17QAT; NHIC-926QAT; NHRIC-17QAT; NHRIC-926QAT)

60W A19 Max. (NH-26Q; NH-27Q; NH-926Q; NHIC-17/100DWQA; NHR-26Q; NHR-27Q; NHR-926Q)

Compact Fluorescent

See Page 2 for compatible housings and lamps

Compact Fluorescent Retrofit Kits

(1) 13W Twin (NPK-13)

(2) 13W Twin (NPK-13/2L)

(1) 13W Quad/Triple (NPK-13EL)

(1) 18W Quad/Triple (NPK-18EL)

(1) 26W Quad/Triple (NPK-26EL)

Labels and Listings

cULus Listed for Wet Location when used with compatible housing

Fresnel Lens with Plastic Trim

NP-23: Fresnel Lens with White Plastic Trim

NORALIGHTING.

Type

Project

Catalog No.

Lamp/Wattage

Compatible Housings

LINE VOLTAGE

Item Number	Installation Type	Lamp	Dimensions
NH-26Q	Non-IC New Construction	60W A19 Max.	W: 7" L: 10-1/8" H: 7-1/2"
NH-27Q	Non-IC Shallow New Constr.	60W A19 Max.	W: 7" L: 10-1/8" H: 5-1/2"
NH-926Q	Non-IC Sloped New Constr.	60W A19 Max.	W: 9-1/2" L: 13" H: 7"
NHIC-17/100DWQA	IC Double Wall AT New Const.	60W A19 Max.	W: 9-1/8" L: 12-1/2" H: 7-3/4"
NHIC-17QAT	IC Air-Tight New Construction	40W A19 Max.	W: 7" L: 10-1/8" H: 7-1/2"
NHIC-27QAT	IC Air-Tight Shallow NC	25W A19 Max.	W: 7" L: 10-1/8" H: 5-1/2"
NHIC-926QAT	IC Air-Tight Sloped NC	40W A19 Max.	W: 7-1/8" L: 13" H: 7-1/2"
NHR-26Q	Non-IC Remodel Housing	60W A19 Max.	W: 6-3/4" L: 13-3/4" H: 7-1/2"
NHR-27Q	Non-IC Shallow Remodel	60W A19 Max.	W: 6-3/4" L: 13-3/4" H: 5-1/2"
NHR-926Q	Non-IC Sloped Remodel	60W A19 Max.	W: 7-1/8" L: 13" H: 7-1/2" W:
NHRIC-17QAT	IC Air-Tight Remodel Housing	40W A19 Max.	6-3/4" L: 13-3/4" H: 7-1/2"
NHRIC-27QAT	IC Air-Tight Shallow Remodel	25W A19 Max.	W: 6-3/4" L: 13-3/4" H: 5-1/2"
NHRIC-926QAT	IC Air-Tight Sloped Remodel	40W A19 Max.	W: 7-1/8" L: 13" H: 7-1/2"

COMPACT FLUORESCENT

SEE PAGE 2 FOR COMPATIBLE HOUSINGS AND LAMPS

COMPACT FLUORESCENT RETROFIT KITS

NPK-13	Retrofit Kit, Magnetic	(1) 13W Twin	Dia: 5-15/16" H: 5-1/2"
NPK-13/2L	Retrofit Kit, Magnetic	(2) 13W Twin	Dia: 5-15/16" H: 5-1/2"
NPK-13EL	Retrofit Kit, Electronic	(1) 13W Q/T	Dia: 5-15/16" H: 5-1/2"
NPK-18EL	Retrofit Kit, Electronic	(1) 18W Q/T	Dia: 5-15/16" H: 5-1/2"
NPK-26EL	Retrofit Kit, Electronic	(1) 26W Q/T	Dia: 5-15/16" H: 5-1/2"


NORALIGHTING.

6505 Gayhart St., Commerce, CA 90040
 www.noralighting.com • Specifications subject to change without notice. © 2011
 Phone: 800.686.6672 • FAX: 800.500.9955 • e-mail: nora@noralighting.com

NP-23

Fresnel Lens with Plastic Trim

TRIM DIMENSIONS



Trim OD: 8"

FEATURES

Trim

High grade fresnel lens attached to plastic trim. Lens can be easily removed by hand without tools from below the ceiling for relamping.

Mounting

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

Compatible Housings

Compatible with Line Voltage, Compact Fluorescent, and CFL Retrofits. See individual specification sheets for more information.

Lamp

Line Voltage

See Page 1 for compatible housings and lamps

Compact Fluorescent

(1) 13W-18W Quad/Triple (NHPIC-926 Series; NHRPIC-926 Series)

(1) 13W-26W Quad (NHP Series; NHPH Series; NHPIC Series; NHRP Series; NHRPH Series; NHRPIC Series)

(1) 13W-26W Quad/Triple (NHP-926 Series; NHRP-926 Series)

(1) 13W-42W Triple (NHP Series; NHPH Series; NHPIC Series; NHRP Series; NHRPH Series; NHRPIC Series)

(2) 13W-26W Quad (NHP-2L Series; NHPH Series; NHPIC-2L Series; NHRP-2L Series; NHRPH Series)

Compact Fluorescent Retrofit Kits

See Page 1 for compatible housings and lamps

Labels and Listings

cULus Listed for Wet Location when used with compatible housing

Fresnel Lens with Plastic Trim

NP-23: Fresnel Lens with White Plastic Trim

NORALIGHTING.

Type

Project

Catalog No.

Lamp/Wattage

Compatible Housings

COMPACT FLUORESCENT

Item Number	Installation Type	Lamp	Dimensions
NHP-13/2LEL	Non-IC New Construction	(2) 13W Quad	W: 7-5/8" L: 14" H: 7-3/8"
NHP-13/2LQ	Non-IC New Construction	(2) 13W Q/Twin	W: 7-5/8" L: 14" H: 7-3/8"
NHP-13EL	Non-IC New Construction	(1) 13W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHP-13M	Non-IC New Construction	(1) 13W Quad	W: 7-5/8" L: 14" H: 7-3/8"
NHP-18/2LEL	Non-IC New Construction	(2) 18W Quad	W: 7-5/8" L: 14" H: 7-3/8"
NHP-18EL	Non-IC New Construction	(1) 18W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHP-26/2LEL	Non-IC New Construction	(2) 26W Quad	W: 7-5/8" L: 14" H: 7-3/8"
NHP-26EL	Non-IC New Construction	(1) 26W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHP-2642EL	Non-IC New Construction	(1) 26-42W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHP-926/13EL	Non-IC Sloped New Const.	(1) 13W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHP-926/18EL	Non-IC Sloped New Const.	(1) 18W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHP-926/2642EL	Non-IC Sloped New Const.	(1) 26-32W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPH-113SEL	Non-IC Shallow New Const.	(1) 13W Q/T	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-118SEL	Non-IC Shallow New Const.	(1) 18W Q/T	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-2642SEL	Non-IC Shallow New Const.	(1) 26-42W Q/T	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-213SEL	Non-IC Shallow New Const.	(2) 13W Quad	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-218SEL	Non-IC Shallow New Const.	(2) 18W Quad	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-226SEL	Non-IC Shallow New Const.	(2) 26W Quad	W: 8" L: 12-1/2" H: 4-3/8"
NHPIC-13/2LEL	IC Double Wall New Const.	(2) 13W Quad	W: 9-1/2" L: 13" H: 7-1/2"
NHPIC-13/2LQ	IC Double Wall New Const.	(2) 13W Q/Twin	W: 9-1/2" L: 13" H: 7-1/2"
NHPIC-13EL	IC New Construction	(1) 13W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-13ELAT	IC Air-Tight New Construction	(1) 13W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-13MQ	IC New Construction	(1) 13W Quad	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-18ATE2	IC Air-Tight New Construction	(1) 18W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-18ELAT	IC Air-Tight New Construction	(1) 18W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-26ATE2	IC Air-Tight New Construction	(1) 26W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-26ELAT	IC Air-Tight New Construction	(1) 26W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-2642ELAT	IC Double Wall AT New Const.	(1) 26-42W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-926/13EAT	IC AT Sloped New Const.	(1) 13W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-926/18EAT	IC AT Sloped New Const.	(1) 18W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-926/26EAT	IC AT Sloped New Const.	(1) 26W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-926/32EAT	IC Double Wall AT Sloped NC	(1) 26-32W Q/T	W: 7-5/8" L: 14" H: 7-3/4"
NHRP-13/2LEL	Non-IC Remodel Housing	(2) 13W Quad	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRP-13/2LQ	Non-IC Remodel Housing	(2) 13W Q/T	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRP-13EL	Non-IC Remodel Housing	(1) 13W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRP-13MQ	Non-IC Remodel Housing	(1) 13W Quad	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRP-18/2LEL	Non-IC Remodel Housing	(2) 18W Quad	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRP-18EL	Non-IC Remodel Housing	(1) 18W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRP-26/2LEL	Non-IC Remodel Housing	(2) 26W Quad	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRP-2642EL	Non-IC Remodel Housing	(1) 26-42W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRP-926/13EL	Non-IC Sloped Remodel	(1) 13W Q/T	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRP-926/18EL	Non-IC Sloped Remodel	(1) 18W Q/T	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRP-926/2642EL	Non-IC Sloped Remodel	(1) 26-32W Q/T	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRPH-113SEL	Non-IC Shallow Remodel	(1) 13W Q/T	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-118SEL	Non-IC Shallow Remodel	(1) 18W Q/T	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-2642SEL	Non-IC Shallow Remodel	(1) 26-42W Q/T	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-213SEL	Non-IC Shallow Remodel	(2) 13W Quad	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-218SEL	Non-IC Shallow Remodel	(2) 18W Quad	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-226SEL	Non-IC Shallow Remodel	(2) 26W Quad	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPIC-13EL	IC Remodel Housing	(1) 13W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-13ELAT	IC Air-Tight Remodel Housing	(1) 13W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-13MQ	IC Remodel Housing	(1) 13W Quad	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-18EL	IC Remodel Housing	(1) 18W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-18ELAT	IC Air-Tight Remodel Housing	(1) 18W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-26ATE2	IC Air-Tight Remodel Housing	(1) 26W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-26ELAT	IC Air-Tight Remodel Housing	(1) 26W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-92613EAT	IC Air-Tight Sloped Remodel	(1) 13W Q/T	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRPIC-92618EAT	IC Air-Tight Sloped Remodel	(1) 18W Q/T	W: 6-1/4" L: 13-1/2" H: 7-3/8"
NHRPIC-92626EAT	IC Air-Tight Sloped Remodel	(1) 26W Q/T	W: 6-1/4" L: 13-1/2" H: 7-3/8"

NORALIGHTING.

6505 Gayhart St., Commerce, CA 90040
 www.noralighting.com • Specifications subject to change without notice. © 2011
 Phone: 800.686.6672 • FAX: 800.500.9955 • e-mail: nora@noralighting.com