

# NT-22

## 6" Albalite Lens with Trim

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** High grade albalite lens attached to trim. Lens can be easily removed by hand without tools from below the ceiling for relamping.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

### LAMP

Line Voltage

25W A19 Maximum (NHIC-27QAT; NHRIC-27QAT)

40W A19 Maximum (NHIC-17QAT; NHRIC-17QAT)

60W A19 Max. (NH-26Q; NH-27Q; NHIC-17/100DWQA; NHR-26Q; NHR-27Q)

Sloped Line Voltage

40W A19 Maximum (NHIC-926DWQAT; NHIC-926QAT; NHRIC-926QAT)

### LABELS AND LISTINGS

- cULus Listed for Wet Location when used with compatible housing.



### PRODUCT IMAGES AND DIMENSIONS



NT-22




NT-22BZ



NT-22N



NP-22



### 6" Albalite Lens with Trim

Catalog No.

**NT-22** = Albalite Lens with White Metal Trim

**NT-22BZ** = Albalite Lens with Bronze Metal Trim

**NT-22N** = Albalite Lens with Natural Metal Trim

**NP-22** = Albalite Lens with White Plastic Trim

### Compatible Housings

Catalog No.

**NH-26Q** = Non-IC New Construction / 60W max

**NHR-26Q** = Non-IC Remodel / 60W max

**NHIC-17/100DWQA** = IC Air-Tight Double Wall New Construction / 60W max

**NHIC-17QAT** = IC Air-Tight New Construction / 40W max

**NHRIC-17QAT** = IC Air-Tight Remodel / 40W max

**NH-27Q** = Shallow Non-IC New Construction / 60W max

**NHR-27Q** = Shallow Non-IC Remodel / 60W max

**NHIC-27QAT** = Shallow IC Air-Tight New Construction / 25W max

**NHRIC-27QAT** = Shallow IC Air-Tight Remodel / 25W max

**NHIC-926DWQAT** = Sloped IC Air-Tight New Construction / 40W max

**NHIC-926QAT** = Sloped IC Air-Tight New Construction / 40W max

**NHRIC-926QAT** = Sloped IC Air-Tight Remodel / 40W max

Example: **NT-22** = 6" Albalite Lens with White Metal Trim