


Type
Project
Catalog No.
Lamp/Wattage

**NT-45 / NT-46
Wall Wash Eyelid with Baffle**

TRIM DIMENSIONS



Trim OD: 7-1/4"
Height: 2-3/4"

FEATURES

Trim
Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare and plastic ring with steel half moon face. Trim may also be used with custom combination of ring finishes.

Mounting
Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22).

Compatible Housings
Compatible with Line Voltage and Compact Fluorescent housings. See individual specification sheets for more information.

Lamp
Line Voltage
75W BR30/PAR30 Max. (NH-26Q; NH-27Q; NHIC-17/100DWQA; NHIC-17QAT; NHIC-27QAT; NHR-26Q; NHR-27Q; NHRIC-17QAT; NHRIC-27QAT)

Compact Fluorescent
See page 2 for compatible housings and lamps
Vertical Shallow Compact Fluorescent
See page 2 for compatible housings and lamps
Horizontal Shallow Compact Fluorescent
See page 2 for compatible housings and lamps
Compact Fluorescent Retrofit Kits
See page 2 for compatible housings and lamps

Labels and Listings
cULus Listed for Damp Location when used with compatible housing.

Compatible Housings

LINE VOLTAGE

Item Number	Installation Type	Lamp	Dimensions
NH-26Q	Non-IC New Construction	75W Max.	W: 7" L: 10-1/8" H: 7-1/2"
NH-27Q	Non-IC Shallow New Const.	75W Max.	W: 7" L: 10-1/8" H: 5-1/2"
NHIC-17/100DWQA	IC Double Wall AT New Const.	75W Max.	W: 9-1/8" L: 12-1/2" H: 7-3/4"
NHIC-17QAT	IC Air-Tight New Construction	75W Max.	W: 7" L: 10-1/8" H: 7-1/2"
NHIC-27QAT	IC Air-Tight Shallow New Co.	75W Max.	W: 7" L: 10-1/8" H: 5-1/2"
NHR-26Q	Non-IC Remodel Housing	75W Max.	W: 6-3/4" L: 13-3/4" H: 7-1/2"
NHRIC-17QAT	IC Air-Tight Remodel Housing	75W Max.	W: 6-3/4" L: 13-3/4" H: 7-1/2"
NHRIC-27QAT	IC Air-Tight Shallow Remodel	75W Max.	W: 6-3/4" L: 13-3/4" H: 5-1/2"


Wall Wash Eyelid with Baffle

- NT-45: White Wall Wash Eyelid with Black Baffle and White Plastic Ring
- NT-46: White Wall Wash Eyelid with White Baffle and White Plastic Ring

Type
Project
Catalog No.
Lamp/Wattage

NT-45 / NT-46 Wall Wash Eyelid with Baffle

TRIM DIMENSIONS



Trim OD: 7-1/4"
Height: 2-3/4"

FEATURES

Trim

Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare and plastic ring with steel half moon face. Trim may also be used with custom combination of ring finishes.

Mounting

Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22).

Compatible Housings

Compatible with Line Voltage and Compact Fluorescent housings. See individual specification sheets for more information.

Lamp

Line Voltage

See page 1 for compatible housings and lamps

Compact Fluorescent

13W-26W Quad (NHP Series; NHPIC Series; NHRP Series; NHRPIC Series)
13W-42W Triple (NHP Series; NHPIC Series; NHPIC Series; NHPIC Series;
NHRP Series; NHRPIC Series; NHRPIC Series)

Vertical Shallow Compact Fluorescent

(1) 13W-26W Triple Tube (NHPIC-613ELAT; NHPIC-618ELAT; NHPIC-626ELAT;
NHRPIC-613ELAT; NHRPIC-618ELAT; NHRPIC-626ELAT)

Horizontal Shallow Compact Fluorescent

(1) 13W-42W Triple Tube (NHPH-113SEL; NHPH-118SEL; NHPH-2642SEL;
NHRPH-113SEL; NHRPH-118SEL; NHRPH-2642SEL)
(2) 13W-26W Quad Tube (NHPH-213SEL; NHPH-218SEL; NHPH-226SEL;
NHRPH-213SEL; NHRPH-218SEL; NHRPH-226SEL)

Compact Fluorescent Retrofit Kits

(1) 13W 2-Pin Twin (NPK-13)
(2) 13W 2-Pin Twin (NPK-13/2L)
(1) 13W 4-Pin Quad/Triple (NPK-13EL)
(1) 18W 4-Pin Quad/Triple (NPK-18EL)
(1) 26W 4-Pin Quad/Triple (NPK-26EL)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

Wall Wash Eyelid with Baffle

NT-45: White Wall Wash Eyelid with Black Baffle and White Plastic Ring

NT-46: White Wall Wash Eyelid with White Baffle and White Plastic Ring

Compatible Housings

COMPACT FLUORESCENT

Item Number	Installation Type	Lamp	Dimensions
NHP-13EL	Non-IC New Construction	13W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHP-13M	Non-IC New Construction	13W Q/Twin	W: 7-5/8" L: 14" H: 7-3/8"
NHP-18EL	Non-IC New Construction	18W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHP-2642EL	Non-IC New Construction	26-42W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-13EL	IC New Construction	13W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-13ELAT	IC Air-Tight New Construction	13W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-13MQ	IC New Construction	13W Q/Twin	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-18EL	IC New Construction	18W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-18ELAT	IC Air-Tight New Construction	18W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-26ATE2	IC Air-Tight New Construction	26W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-26ELAT	IC Air-Tight New Construction	26W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHPIC-2642ELAT	IC Double Wall AT New Const.	26-42W Q/T	W: 7-5/8" L: 14" H: 7-3/8"
NHRP-13EL	Non-IC Remodel Housing	13W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRP-13MQ	Non-IC Remodel Housing	13W Q/Twin	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRP-18EL	Non-IC Remodel Housing	18W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRP-2642EL	Non-IC Remodel Housing	26-42W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-13EL	IC Remodel Housing	13W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-13ELAT	IC Air-Tight Remodel Housing	13W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-13MQ	IC Remodel Housing	13W Q/Twin	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-18EL	IC Remodel Housing	18W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-18ELAT	IC Air-Tight Remodel Housing	18W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-26ATE2	IC Air-Tight Remodel Housing	26W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"
NHRPIC-26ELAT	IC Air-Tight Remodel Housing	26W Q/T	W: 6-3/4" L: 13-1/2" H: 7-3/8"

VERTICAL SHALLOW COMPACT FLUORESCENT

NHPIC-613ELAT	IC Air-Tight Shallow New Con.	(1) 13W T	W: 7" L: 10-1/8" H: 5-1/2"
NHPIC-618ELAT	IC Air-Tight Shallow New Con.	(1) 18W T	W: 7" L: 10-1/8" H: 5-1/2"
NHPIC-626ELAT	IC Air-Tight Shallow New Con.	(1) 26W T	W: 7" L: 10-1/8" H: 5-1/2"
NHRPIC-613ELAT	IC Air-Tight Shallow Remodel	(1) 13W T	W: 6-3/4" L: 13-3/4" H: 5-1/2"
NHRPIC-618ELAT	IC Air-Tight Shallow Remodel	(1) 18W T	W: 6-3/4" L: 13-3/4" H: 5-1/2"
NHRPIC-626ELAT	IC Air-Tight Shallow Remodel	(1) 26W T	W: 6-3/4" L: 13-3/4" H: 5-1/2"

HORIZONTAL SHALLOW COMPACT FLUORESCENT

NHPH-113SEL	Non-IC Shallow New Const.	(1) 13W T	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-118SEL	Non-IC Shallow New Const.	(1) 18W T	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-2642SEL	Non-IC Shallow New Const.	(1) 26-42W T	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-213SEL	Non-IC Shallow New Const.	(2) 13W Q	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-218SEL	Non-IC Shallow New Const.	(2) 18W Q	W: 8" L: 12-1/2" H: 4-3/8"
NHPH-226SEL	Non-IC Shallow New Const.	(2) 26W Q	W: 8" L: 12-1/2" H: 4-3/8"
NHRPH-113SEL	Non-IC Shallow Remodel	(1) 13W T	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-118SEL	Non-IC Shallow Remodel	(1) 18W T	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-2642SEL	Non-IC Shallow Remodel	(1) 26-42W T	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-213SEL	Non-IC Shallow Remodel	(2) 13W Q	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-218SEL	Non-IC Shallow Remodel	(2) 18W Q	W: 6-3/4" L: 13-7/8" H: 4-3/8"
NHRPH-226SEL	Non-IC Shallow Remodel	(2) 26W Q	W: 6-3/4" L: 13-7/8" H: 4-3/8"

COMPACT FLUORESCENT RETROFIT KITS

NPK-13	Retrofit Kit, Magnetic	(1) 13W Twin	Dia: 5-15/16" H: 5-1/2"
NPK-13/2L	Retrofit Kit, Magnetic	(2) 13W Twin	Dia: 5-15/16" H: 5-1/2"
NPK-13EL	Retrofit Kit, Electronic	(1) 13W Q/T	Dia: 5-15/16" H: 5-1/2"
NPK-18EL	Retrofit Kit, Electronic	(1) 18W Q/T	Dia: 5-15/16" H: 5-1/2"
NPK-26EL	Retrofit Kit, Electronic	(1) 26W Q/T	Dia: 5-15/16" H: 5-1/2"