

# NT-5001

## 5" Baffle Splay Trim with Flange

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun high grade reflector and baffle with deep grooves to reduce aperture glare.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from plate within housing (if applicable), and mount socket in trim's neck.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP

75W BR30/PAR30 (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

### LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



NT-5001B




NT-5001BZ



NT-5001N



NT-5001W



## 5" Baffle Splay Trim with Flange

Catalog No. \_\_\_\_\_

**NT-5001B** = Black Aluminum Baffle with White Flange

**NT-5001BZ** = Bronze Aluminum Baffle with Bronze Flange

**NT-5001N** = Natural Metal Aluminum Baffle Splay with Natural Metal Flange

**NT-5001W** = White Aluminum Baffle Splay with White Flange

## Compatible Housings

Catalog No. \_\_\_\_\_

**NHIC-501QAT** = 5" IC Air-Tight New Construction / 75W max

**NHRIC-504QAT** = 5" IC Air-Tight Remodel / 75W max

**NH-501Q** = 5" Non-IC New Construction / 75W max

**NHR-504Q** = 5" Non-IC Remodel / 75W max

Example: **NT-5001B** = Black Aluminum Baffle with White Flange