

# NT-5022

## Albalite Lens with Metal Trim and Bracket

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** High grade albalite lens attached to metal trim with a bracket. Bracket includes two socket positions for optimum light control and output.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP

#### Line Voltage:


40W A19 Maximum (NHIC-501QAT; NHRIC-504QAT)

### LABELS AND LISTINGS

cULus Listed for Wet Locations when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



### Albalite Lens with Metal Trim and Bracket

Catalog No. \_\_\_\_\_

**NT-5022W** = Albalite Lens with White Metal Trim and Bracket

### Compatible Housings

Catalog No. \_\_\_\_\_

**NHIC-501QAT** = 5" IC Air-Tight New Construction / 40W max

**NHRIC-504QAT** = 5" IC Air-Tight Remodel / 40W max

Example: **NT-5022W** = 5" Albalite Lens with White Trim and Bracket