

NT-5030

5" BR30/PAR30 Open Metal Trim

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Metal trim with 3-7/8" open center. Bracket includes two socket positions for optimum light control and output.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

75W BR30/PAR30 (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

GU24

26W GU24 (NHIC-5G24ATFL)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS




NT-5030BZ



NT-5030C



NT-5030W



5" BR30/PAR30 Open Metal Trim

Catalog No. _____

NT-5030BZ = Bronze Open Metal Trim

NT-5030C = Chrome Open Metal Trim

NT-5030W = White Open Metal Trim

Compatible Housings

Line Voltage

Catalog No. _____

NH-501Q = 5" Non-IC New Construction Housing / 75W max

NHR-504Q = 5" Non-IC Remodel Housing / 75W max

NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 75W max

NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 75W max

GU24

Catalog No. _____

NHIC-5G24ATFL = 5" IC Air-Tight GU24 New Construction / 26W max

Example: **NT-5030BZ** = Bronze Open Metal Trim