

NT-5045

5" Wall Wash Eyelid with Baffle

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare and white flange with steel half moon face.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP


75W BR30/PAR30 (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



5" Wall Wash Eyelid with Baffle

Catalog No. _____

NT-5045W = White Wall Wash Eyelid with White Baffle and White Flange

Compatible Housings

Catalog No. _____

NH-501Q = 5" Non-IC New Construction Housing / 75W max
NHR-504Q = 5" Non-IC Remodel Housing / 75W max
NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 75W max
NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 75W max

Example: **NT-5045W** = 5" White Wall Wash Eyelid with White Baffle and White Flange