

NT-5048

5" Stepped Baffle with Regressed Eyeball

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.040 baffle with deep grooves to reduce aperture glare. Metal trim with adjustable eyeball can be rotated 360° horizontally and 35° vertically. Eyeball includes two socket positions for optimum light control and output. Separate trim ring available in plastic or metal, may also be used with custom combination of ring finishes.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

50W PAR30 Maximum (NHIC-527QAT; NHRIC-527QAT)

75W BR30/PAR30 Maximum (NH-5010; NHIC-501QAT; NHR-5040; NHRIC-504QAT)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing




PRODUCT IMAGES AND DIMENSIONS



NT-5048B



NT-5048W



5" Stepped Baffle with Regressed Eyeball

Catalog No. _____

NT-5048B = Black Stepped Baffle with White Regressed Eyeball and White Plastic Ring

NT-5048W = White Stepped Baffle with White Regressed Eyeball and White Plastic Ring

Compatible Housings

Catalog No. _____

NH-5010 = 5" Non-IC New Construction Housing / 75W max

NHR-5040 = 5" Non-IC Remodel Housing / 75W max

NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 75W max

NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 75W max

NHIC-527QAT = 5" Shallow IC Air-Tight New Construction Housing / 50W max

NHRIC-527QAT = 5" Shallow IC Air-Tight Remodel Housing / 50W max

Example: **NT-5048B** = Black Stepped Baffle with White Regressed Eyeball and White Plastic Ring