

NT-5071

5" R20/PAR20 Eyeball

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Adjustable metal trim can be rotated 358° horizontally and 30° vertically. Eyeball includes two socket positions for optimum light control and output.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

50W R20/PAR20 Maximum (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

LABELS AND LISTINGS


· cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



NT-5071W



5" R20/PAR20 Eyeball

Catalog No. _____

NT-5071W = White R20/PAR20 Eyeball

Compatible Housings

Catalog No. _____

NH-501Q = 5" Non-IC New Construction Housing / 50W max
NHR-504Q = 5" Non-IC Remodel Housing / 50W max
NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 50W max
NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 50W max

Example: **NT-5071W** = White R20/PAR20 Eyeball