

# NTA-730

## Specular Clear Reflector with Metal Baffle and White Flange

Type

Project

Catalog No.

Notes

### FEATURES

**Trim:** Precision spun 0.050 aluminum high grade specular clear reflector with metal baffle and white flange. Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Socket can be mounted directly to reflector without bracket.

### COMPATIBLE LAMP / HOUSINGS

#### Line Voltage:

60W A19 Maximum (NH-26Q; NH-26QNB; NHIC-17QAT; NHIC-17QNBAT; NHR-26Q; NHRIC-17QAT; NHRIC-17QNBAT)

75W BR/PAR30 Maximum (NH-26Q; NH-26QNB; NHIC-17QAT; NHIC-17QNBAT; NHRIC-17QAT; NHRIC-17QNBAT; NHR-26Q)

100W A19/BR40/PAR38 Maximum (NH-26Q; NH-26QNB; NHIC-17/100DWQA; NHR-26Q)

150W BR40/PAR38 Maximum (NH-26Q; NH-26QNB; NHR-26Q)

### LABELS AND LISTINGS

\* cULus Listed for Damp Location when used with compatible housing




### PRODUCT IMAGES & DIMENSIONS



NTA-730B



NTA-730W



## 6" Specular Clear Reflector with Metal Baffle and White Flange

Catalog No.

**NTA-730B** = 6" Specular Clear Reflector with Black Metal Baffle and White Flange

**NTA-730W** = 6" Specular Clear Reflector with White Metal Baffle and White Flange

### Compatible Housings

Catalog No.

**NH-26Q** = Non-IC New Construction / 150W max

**NH-26QNB** = Non-IC New Construction / 150W max

**NHR-26Q** = Non-IC Remodel / 100W max

**NHIC-17/100DWQA** = IC Air-Tight Double Wall New Construction / 100W max

**NHRIC-17QAT** = IC Air-Tight New Construction / 75W max

**NHRIC-17QAT** = IC Air-Tight Remodel / 75W max

**NHIC-17QNBAT** = IC Air-Tight New Construction / 75W max

**NHRIC-17QNBAT** = IC Air-Tight Remodel / 75W max

Example: **NTA-730B** = 6" Specular Clear Reflector with Black Metal Baffle and White Flange