

NTM-29

6" BR/PAR30 Stepped Baffle with Metal Ring

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare and metal ring. Trim may also be used with custom combination of ring finishes.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

LAMP

75W BR/PAR30 Maximum (NH-260; NH-270; NHIC-17QAT; NHIC-17/100DWQA; NHIC-27QAT NHR-260; NHR-270; NHRIC-17QAT; NHRIC-27QAT)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing.




PRODUCT IMAGES AND DIMENSIONS



NTM-29BW



NTM-29WW



6" BR/PAR30 Stepped Baffle with Metal Ring

Catalog No.

NTM-29BW = Black Stepped Baffle with White Metal Ring

NTM-29WW = White Stepped Baffle with White Metal Ring

Compatible Housings

Catalog No.

NH-260 = Non-IC New Construction / 75W max

NHR-260 = Non-IC Remodel / 75W max

NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 75W max

NHIC-17QAT = IC Air-Tight New Construction / 75W max

NHRIC-17QAT = IC Air-Tight Remodel / 75W max

NH-270 = Shallow Non-IC New Construction / 75W max

NHR-270 = Shallow Non-IC Remodel / 75W max

NHIC-27QAT = Shallow IC Air-Tight New Construction / 75W max

NHRIC-27QAT = Shallow IC Air-Tight Remodel / 75W max

Example: **NTM-29WW** = White Stepped Baffle with White Metal Ring