


**NTM-38 / NTM-39
Eyeball with Baffle and Metal Trim**

Type
Project
Catalog No.
Lamp/Wattage

TRIM DIMENSIONS



Trim OD: 8"
Eyeball Height: 5-1/8"

FEATURES

Trim

Metal trim with adjustable eyeball can be rotated 90° horizontally and 20° vertically. Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare.

Mounting

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount lamp on eyeball.

Compatible Housings

Compatible with Line Voltage, Sloped Line Voltage, and GU24 housings. See individual specification sheets for more information.

Lamp

Line Voltage

75W BR/PAR30 Maximum (NH-26Q; NH-26QNB; NHIC-17/100DWQA; NHIC-17QAT, NHIC-17QNBAT; NHR-26Q; NHRIC-17QAT; NHRIC-17QNBAT)

Sloped Line Voltage

75W BR/PAR30 Maximum (NH-926Q; NHIC-926/DWQAT; NHIC-926QAT; NHR-926Q; NHRIC-926QAT)

GU24 Compact Fluorescent

15W R30 GU24 (NHIC-6G24ATFL; NHRIC-6G24ATFL)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

Compatible Housings

LINE VOLTAGE		
Item Number	Installation Type	Dimensions
NH-26Q	Non-IC New Construction	W: 7" L: 10-1/8" H: 7-1/2"
NH-26QNB	Non-IC New Construction - No Bracket	W: 7" L: 10-1/8" H: 7-1/2"
NHIC-17/100DWQA	IC Double Wall Air-Tight New Construction	W: 9-1/8" L: 12-1/2" H: 7-3/4"
NHIC-17QAT	IC Air-Tight New Construction	W: 7" L: 10-1/8" H: 7-1/2"
NHIC-17QNBAT	IC Air-Tight New Const. - No Bracket	W: 7" L: 10-1/8" H: 7-1/2"
NHR-26Q	Non-IC Remodel Housing	W: 6-3/4" L: 13-3/4" H: 7-1/2"
NHRIC-17QAT	IC Air-Tight Remodel Housing	W: 6-3/4" L: 13-3/4" H: 7-1/2"
NHRIC-17QNBAT	IC Air-Tight Remodel - No Bracket	W: 6-3/4" L: 13-3/4" H: 7-1/2"
SLOPED LINE VOLTAGE		
NH-926Q	Non-IC New Construction	W: 9-1/2" L: 13" H: 7"
NHIC-926/DWQAT	IC Double Wall Air-Tight New Construction	W: 9-1/2" L: 13" H: 7-3/4"
NHIC-926QAT	IC Air-Tight New Construction	W: 9-1/2" L: 13" H: 7"
NHR-926Q	Non-IC Remodel Housing	W: 7-1/8" L: 13" H: 7-1/2"
NHRIC-926QAT	IC Air-Tight Remodel Housing	W: 7-1/8" L: 13" H: 7-1/2"
GU24 COMPACT FLUORESCENT		
NHIC-6G24ATFL	IC Air-Tight New Construction	W: 7" L: 10-1/8" H: 7-1/2"
NHRIC-6G24ATFL	IC Air-Tight Remodel Housing	W: 6-3/4" L: 13-3/4" H: 7-1/2"

Eyeball with Baffle and Metal Trim

NTM-38: White Eyeball with Black Baffle and White Metal Trim

NTM-39: White Eyeball with White Baffle and White Metal Trim