

# NTM-40 / NTM-41

## 6" BR40/PAR38 Stepped Baffle with Ring

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Precision spun 0.050 aluminum baffle with deep grooves to reduce aperture glare and regressed albalite lens. Separate trim ring available in plastic or metal, may also be used with custom combination of ring finishes.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount lamp into gimbal ring.

### COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

### LAMP

- 100W BR40/PAR38 Maximum (NHIC-17/100DWQA)
- 150W BR40/PAR38 Maximum (NH-260; NHR-260)

### LABELS AND LISTINGS

- cULus Listed for Damp Location when used with compatible housing.



### PRODUCT IMAGES AND DIMENSIONS



NTM-40



NTM-40B




NTM-41BZ



NTM-41



NTM-41N



## 6" BR40/PAR38 Stepped Baffle with Ring

Catalog No.

- NTM-40 = Black Stepped Baffle with White Plastic Ring
- NTM-40/OV = Black Stepped Baffle with Oversize White Plastic Ring
- NTM-40/2R = Black Stepped Baffle with Two White Plastic Rings (Regular and Oversize)
- NTM-40B = Black Stepped Baffle with Black Plastic Ring
- NTM-41 = White Stepped Baffle with White Plastic Ring
- NTM-41/OV = White Stepped Baffle with Oversize White Plastic Ring
- NTM-41/2R = White Stepped Baffle with Two White Plastic Rings (Regular and Oversize)
- NTM-41BZ = Bronze Stepped Baffle with Bronze Metal Ring
- NTM-41N = White Stepped Baffle with Natural Metal Ring

## Compatible Housings

Catalog No.

- NH-260 = Non-IC New Construction / 150W max
- NHR-260 = Non-IC Remodel / 150W max
- NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 100W max

Example: NTM-40 = 6" Black Stepped Baffle with White Plastic Ring